
Print Page Return to search STUANUA CAN Management of the Management of the Provenuer -

Product Number:	20988
Order Abbreviation:	FP14/865/ECO
General Description:	14W, T5 PENTRON fluorescent lamp, 6500K color temperature, 85 CRI, rare earth phosphor, ECOLOGIC

Product Information		
Abbrev. With Packaging Info.	FP14865ECO 40/CS 1/SKU	
Actual Length (in)	22.2	
Actual Length (mm)	563.2	
Average Rated Life (hr)	20000	
Base	Miniature Bipin	
Bulb	Т5	
Color Rendering Index (CRI)	85	
Color Temperature/CCT (K)	6500	
Diameter (in)	0.67	
Diameter (mm)	17.0	
Family Brand Name	PENTRON® HIGH OUTPUT	
Initial Lumens at 25C	1100	
Initial Lumens at 35C	1300	
Mean Lumens at 25C	1209	
Mean Lumens at 35C	1235	
Nominal Length (in)	24	
Nominal Wattage (W)	14.00	

Additional Product Information	
Product Documents, Graphs, and Images	
Packaging Information	



Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Lumen output and life rated on high frequency operation.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- There is a NEMA supported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal end-of-life phenomenon. This end-of-life phenomenon can resultin one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMA recommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this system are yet to be defined by ANSI. For additional information refer to NEMA papers on their WEBSITE at www.NEMA.org.
- SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit www.lamprecycle.org

Print Page