



## Universals 14W Med SLS ALTO 1CT

### Product family description

Screw-in Compact Fluorescent with an electronic, integral ballast. Direct replacement for incandescent, offering energy savings, high color rendering and long life.

### Features/Benefits

- Energy Savings - Saves up to 75% in electricity costs compared to incandescent lamps.
- Provides soft, white light.
- Ideal for uses in table lamps and hard to reach fixtures.
- Available in 60, 75 and 100 Watt equivalents.
- Amalgam Technology - Provides stable light output over a broad range of temperatures.
- ENERGY STAR Pending on 15,000 hr version.
- Super Long Life - 10,000 to 15,000 hrs.

### Applications

- Ideal for table lamps, wall sconces, recessed lighting, ceiling fixtures, surface mounted light fixtures and hanging lamps.

### Notes

- The use of Amalgam Technology results in relatively stable light output across a broad range of ambient temperatures and operating positions. (216)
- All Marathon™ lamps are suitable for indoor or outdoor use down to -10°F. Outdoor use requires a weather-protected fixture. All these products comply with part 18 of the FCC rules. These products may cause interference with AM radios, cordless telephones, and remote control devices. Interference may be caused after a brief 90-second lamp warm-up period. If interference continues, relocate the lamp away from the device or plug into a different outlet. (217)
- All lamps are electronically ballasted and designed for 120 volt operation. Lamps operated in extreme environments will have reduced life (ie. recessed or enclosed lighting fixtures with elevated line voltage). Caution: except for lamps marked dimmable, do not use with dimmers. Before using these lamps with electronic timing or photocell devices, check to determine whether the device is compatible with compact fluorescent lamps. Use with incompatible devices will result in premature lamp failure. These products are UL listed. (218)
- Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. (230)
- Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions. (231)

Product data	
Product Number	146910
Full product name	Universals 14W Med SLS ALTO 1CT
Ordering Code	SLS 14 MARATHON UNIV ALTO
Pack type	1 Lamp in a Folding Carton
Pieces per Sku	1
Skus/Case	6
Pack UPC	046677146917
EAN2US	
Case Bar Code	50046677146912
Successor Product number	
Base	Medium [Single Contact Medium Screw]
Bulb	SLS
Packing Type	1CT [1 Lamp in a Folding Carton]
Packing Configuration	6
Feature	ALTO®
Rated Avg. Life [3 hr Start]	10000 hr
Ordering Code	SLS 14 MARATHON UNIV ALTO
Pack UPC	046677146917
Case Bar Code	50046677146912
Energy Saving	Energy Saving
Watts	14W
Color Rendering Index	82 Ra8
Color Temperature	2700 K
Initial Lumens	860 Lm
Max Overall Length (MOL) - C	4.94 in
Product Number	146910



Univ SLS



Base Medium



Energy Saving Energy Saving

