

Cold Cathodes

800.324.1496 + www.tcpi.com

A Little or A Lot






Cold Cathode lamps are excellent for dimming and rapid cycling applications.

Your Name in Lights

Our globes are ideal for decorative, marquee, porte-cocheres, and sign boards – anywhere you need some fun attention.

Mood Light

R20s, R30s and Flat Pars work great in recessed can applications and down lighting – they're ideal for decorative and porte-cocheres too!

ITEM NUMBER	ITEM DESCRIPTION	LAMP WATTS	INCANDESCENT WATT COMPARISON	INITIAL LUMENS	CCT	CRI	MOL/HEIGHT (INCHES)	DIAMETER/WIDTH (INCHES)	LAMP FINISH	BASE TYPE	
8 WATT FLAME TIP COLD CATHODE 120V, 25,000 HOUR (ALSO AVAILABLE IN CANDELABRA BASE)											
	8TF08CL	8 Watt Cold Cathode Flame Tip Clear	8	35-40	300	2700	82	6.4	2.0	Clear	E26
	8TF08F	8 Watt Cold Cathode Flame Tip Frost	8	35-40	300	2700	82	6.4	2.0	Frost	E26
	8TF08LV	8 Watt Cold Cathode Flame Tip LV	8	35-40	280	2400	82	6.4	2.0	LV	E26
	8TF08WH	8 Watt Cold Cathode Flame Tip White	8	35-40	300	2700	82	6.4	2.0	White	E26
G20 GLOBE COLD CATHODE 120V, 25,000 HOUR (ALSO AVAILABLE IN CANDELABRA BASE)											
	8G2003CL	3 Watt Cold Cathode G20 Globe Clear	3	15-20	120	2700	82	4.0	2.5	Clear	E26
	8G2003F	3 Watt Cold Cathode G20 Globe Frost	3	15-20	120	2700	82	4.0	2.5	Frost	E26
	8G2003WH	3 Watt Cold Cathode G20 Globe White	3	15-20	120	2700	82	4.0	2.5	White	E26
G25 GLOBE COLD CATHODE 120V, 25,000 HOUR (ALSO AVAILABLE IN CANDELABRA BASE)											
	8G2503CL	3 Watt Cold Cathode G25 Globe Clear	3	15-20	120	2700	82	4.3	3.1	Clear	E26
	8G2503F	3 Watt Cold Cathode G25 Globe Frost	3	15-20	120	2700	82	4.3	3.1	Frost	E26
	8G2503WH	3 Watt Cold Cathode G25 Globe White	3	15-20	120	2700	82	4.3	3.1	White	E26
	8G2505CL	5 Watt Cold Cathode G25 Globe Clear	5	25-30	200	2700	82	4.3	3.1	Clear	E26
	8G2505F	5 Watt Cold Cathode G25 Globe Frost	5	25-30	200	2700	82	4.3	3.1	Frost	E26
	8G2505WH	5 Watt Cold Cathode G25 Globe White	5	25-30	200	2700	82	4.3	3.1	White	E26
	8G2508CL	8 Watt Cold Cathode G25 Globe Clear	8	35-40	300	2700	82	4.8	3.1	Clear	E26
	8G2508F	8 Watt Cold Cathode G25 Globe Frost	8	35-40	300	2700	82	4.8	3.1	Frost	E26
	8G2508WH	8 Watt Cold Cathode G25 Globe White	8	35-40	300	2700	82	4.8	3.1	White	E26
G30 GLOBE COLD CATHODE 120V, 25,000 HOUR (ALSO AVAILABLE IN CANDELABRA BASE)											
	8G3008CL	8 Watt Cold Cathode G30 Globe Clear	8	35-40	300	2700	82	5.5	3.7	Clear	E26
	8G3008F	8 Watt Cold Cathode G30 Globe Frost	8	35-40	300	2700	82	5.5	3.7	Frost	E26
	8G3008WH	8 Watt Cold Cathode G30 Globe White	8	35-40	300	2700	82	5.5	3.7	White	E26
R20 REFLECTOR COLD CATHODE 120V, 25,000 HOUR (ALSO AVAILABLE IN CANDELABRA BASE)											
	8R2003CL	3 Watt Cold Cathode R20 Clear	3	15-20	120	2700	82	3.4	2.5	Clear	E26
	8R2003F	3 Watt Cold Cathode R20 Frost	3	15-20	120	2700	82	3.4	2.5	Frost	E26
	8R2005CL	5 Watt Cold Cathode R20 Clear	5	25-30	200	2700	82	4.0	2.5	Clear	E26
	8R2005F	5 Watt Cold Cathode R20 Frost	5	25-30	200	2700	82	4.0	2.5	Frost	E26
	8R2005Y	5 Watt Cold Cathode R20 Yellow	5	25-30	N/A	N/A	N/A	4.0	2.5	Yellow	E26
	8R2005BL	5 Watt Cold Cathode R20 Blue	5	25-30	N/A	N/A	N/A	4.0	2.5	Blue	E26
	8R2005GR	5 Watt Cold Cathode R20 Green	5	25-30	N/A	N/A	N/A	4.0	2.5	Green	E26
	8R2005RD	5 Watt Cold Cathode R20 Red	5	25-30	N/A	N/A	N/A	4.0	2.5	Red	E26
	8R2005P	5 Watt Cold Cathode R20 Pink	5	25-30	N/A	N/A	N/A	4.0	2.5	Pink	E26