

[Return to search](#)[Print Page](#)

Product Number: 29359
Order Abbreviation: CF23EL/PAR38/2700K
General Description: DULUX EL 23W compact fluorescent PAR38 lamp, integral 120V ballast, medium screwbase, 2700K color temperature, 82 CRI, packaged 6/carton

Product Information

Abbrev. With Packaging Info.	CF23ELPAR382700K 6/CS 1/SKU
Average Rated Life (hr)	8000
Base	Medium
Bulb	PAR38
Color Temperature/CCT (K)	2700
Diameter (in)	4.75
Diameter (mm)	121
Industry Standards	CSA, FCC 47CFR PART 18 CONSUMER, UL
Initial Lumens at 25C	1200
Mean Lumens at 25C	760
Maximum Overall Length - MOL (in)	6.25
Maximum Overall Length - MOL (mm)	159
Nominal Wattage (W)	23.00

Additional Product Information

[Product Documents, Graphs, and Images](#)

[Packaging Information](#)



Footnotes

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature for DULUX EL lamps is 0° F, unless otherwise specified in product literature. .
- DULUX ELs meet CSA, FCC and UL requirements.
- Caution: DULUX EL units cannot be used on dimming circuits (unless the lamp is labeled dimmable), emergency exit fixtures or lights, electronic timers, photocells, lighted switches or any other switches that do not meet UL20 Sec. 7.6.15. In outdoor applications, use only in enclosed fixtures to avoid exposure to weather. Use only on

120V, 60 Hz circuits. Never disassemble or modify lamp. Install or remove unit from fixture by grasping plastic base. Best performance achieved when operated at 77degrees F (25 degrees C). 40 Watt lamp is designed for base down orientation only

- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature for DULUX EL lamps is 0 degrees F
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.

[Print Page](#)