


### COMPACT FLUORESCENT LAMPS - PL

Energy Efficient  
Average Life 10,000 Hours


Watts	Item code	Description	Base	Luminous Flux		Dimensions		Color Temp (K)	Case Qty.
				Initial (lm)	Mean (lm)	MOL (in)	Avg. Life (Hours)		
<b>Double Tube 4-Pin G24q-1 Base for Electronic Ballasts-Dimmable</b>									
*10	F01022409201	PL10W/2U/4P/827	G24q-1	600	540	4.13	10000	2700	50
*10	F01022409301	PL10W/2U/4P/835	G24q-1	600	540	4.13	10000	3500	50
*10	F01022409401	PL10W/2U/4P/841	G24q-1	600	540	4.13	10000	4100	50
13	F01322409201	PL13W/2U/4P/827	G24q-1	900	810	5.28	10000	2700	50
13	F01322409301	PL13W/2U/4P/835	G24q-1	900	810	5.28	10000	3500	50
13	F01322409401	PL13W/2U/4P/841	G24q-1	900	810	5.28	10000	4100	50
*13	F01322409601	PL13W/2U/4P/865	G24q-1	860	770	5.28	10000	6500	50
<b>Double Tube 4-Pin G24q-2 Base for Electronic Ballasts-Dimmable</b>									
18	F01822410201	PL18W/2U/4P/827	G24q-2	1200	1080	5.87	10000	2700	50
18	F01822410301	PL18W/2U/4P/835	G24q-2	1200	1080	5.87	10000	3500	50
18	F01822410401	PL18W/2U/4P/841	G24q-2	1200	1080	5.87	10000	4100	50
<b>Double Tube 4-Pin G24q-3 Base for Electronic Ballasts-Dimmable</b>									
26	F02622411201	PL26W/2U/4P/827	G24q-3	1800	1620	6.57	10000	2700	50
26	F02622411301	PL26W/2U/4P/835	G24q-3	1800	1620	6.57	10000	3500	50
26	F02622411401	PL26W/2U/4P/841	G24q-3	1800	1620	6.57	10000	4100	50
*26	F02622411601	PL26W/2U/4P/865	G24q-3	1710	1540	6.57	10000	6500	50

\* Items only available for special orders


All measurements are shown in inches unless noted  
Manage in Accordance with Disposal Laws  
See [www.htr-group.com](http://www.htr-group.com) or 1-888-537-4874




4-Pin Base



G24q-1



G24q-2



G24q-3