

## Slimline F96T12 DX ALTO

Product family description T12 Single Pin Linear Fluorescent Lamps.

## Features/Benefits

• Instant Start.

## **Notes**

- Rated average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Lamp life is appreciably longer if lamps are started less frequently. (202)
- Approximate Initial Lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life, when the output is measured during operation on a reference ballast under standard laboratory conditions. (203)
- For expected lamp lumen output, commercial ballast manufacturers can advise the appropriate Ballast Factor for each of their ballasts when they are informed of the designated lamp. The Ballast Factor is a multiplier applied to the designated lamp lumen output. (204)
- Design Lumens are the approximate lamp lumen output at 40% of the lamp's Rated Average Life. This output is based upon measurements obtained during lamp operation on a reference ballast under standard laboratory conditions. (208)


Product data		
Product Number	372821	
Full product name	Slimline F96T12 DX ALTO	
Ordering Code	F96T12/DX/ALTO	
Pack type	1 Lamp	
Pieces per Sku	1	
Skus/Case	15	
Pack UPC	046677372828	
EAN2US		
Case Bar Code	50046677372823	
Successor Product number		
Base	Single Pin [Single Pin Fluorescent]	
Base Information	Green Base	
Bulb	T12	
Packing Type	1LP [1 Lamp]	



Product data		
Packing Configuration	15	
Type	F96T12	
Feature	ALTO®	
Rated Avg. Life [3 hr Start]	12000 hr	
Ordering Code	F96T12/DX/ALTO	
Pack UPC	046677372828	
Case Bar Code	50046677372823	
Energy Saving	Not Applicable	
Watts	75W	
Mercury (Hg) Content	6.8 mg	
Color Code	57	
Color Rendering Index	84 Ra8	
Color Designation	Daylight Deluxe	
Color Temperature	6500 K	
Initial Lumens	4500 Lm	
Design Mean Lumens	3950 Lm	
Nominal Length [inch]	96	
Product Number	372821	



F-T12-IS FA8/GB



F-T12-IS FA8

