



## F30T12 D HO

Product family description  
Environmentally responsible and excellent  
color rendering.

### Features/Benefits

- Full wattages - will start at - 20°F.
- Argon gas filled - does not shiver at temperatures below 60°F.
- Cool white and daylight color matches existing 48", 60", 72" and 84" lamps.
- National Energy Policy Act (EPA) - meets EPA's exemption for cold temperature application only.

### Applications

- Ideal for outdoor signs, parking garages, refrigerated storage.

### Notes


- Approximate initial lumens are for 800 ma. operation. For 1000 ma. operation, lumens are approximately 10% higher and watts approximately 15% higher. (207)
- Econ-o-watt® lamps are only recommended for use on high power factor lead, indoor ballasts that meet ANSI standards. The lamps are not recommended for use in drafty areas, or locations where the ambient temperature is less than 60°F, except as noted. Also they should not be operated on low power factor ballasts, reduced light or reduced current ballasts, dimming ballasts or emergency system inverter ballasts. (214)
- Rated average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Lamp life is appreciably longer if lamps are started less frequently. (202)
- Approximate Initial Lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life, when the output is measured during operation on a reference ballast under standard laboratory conditions. (203)
- For expected lamp lumen output, commercial ballast manufacturers can advise the appropriate Ballast Factor for each of their ballasts when they are informed of the designated lamp. The Ballast Factor is a multiplier applied to the designated lamp lumen output. (204)
- Design Lumens are the approximate lamp lumen output at 40% of the lamp's Rated Average Life. This output is based upon measurements obtained during lamp operation on a reference ballast under standard laboratory conditions. (208)

---


#### Product data

|                   |             |
|-------------------|-------------|
| Product Number    | 141416      |
| Full product name | F30T12 D HO |

| Product data                 |  |
|------------------------------|--|
| Ordering Code                | F30T12/D/HO                                      |
| Pack type                    | 1 Lamp   |
| Pieces per Sku               | 1  |
| Skus/Case                    | 30   |
| Pack UPC                     | 046677141417                                     |
| EAN2US                       |  |
| Case Bar Code                | 50046677141412                                   |
| Successor Product number     |  |
| Base                         | R17d [Recessed Double Contact Bay (RDC Bay- Flu] |
| Base Information             | Aluminum [Aluminum Base]                         |
| Bulb                         | T12  |
| Execution                    | High Output [High Output]                        |
| Packing Type                 | 1LP [1 Lamp]                                     |
| Packing Configuration        | 30   |
| Type                         | F30T12   |
| Rated Avg. Life [3 hr Start] | 9000 hr  |
| Ordering Code                | F30T12/D/HO                                      |
| Pack UPC                     | 046677141417                                     |
| Case Bar Code                | 50046677141412                                   |
| Energy Saving                | Not Applicable                                   |
| Watts                        | 40W  |
| Color Code                   | 54   |
| Color Rendering Index        | 79 Ra8   |
| Color Designation            | Daylight [Daylight]                              |
| Color Temperature            | 6500 K   |
| Initial Lumens               | 1920 Lm  |
| Design Mean Lumens           | 1590 Lm  |
| Nominal Length [inch]        | 30   |
| Product Number               | 141416   |



F- T12- HO RDC/AL



F- T12- HO RDC

