

[Return to search](#)[Print Page](#)

**Product Number:** 25385

**Order Abbreviation:** F84T12/D/HO

**General Description:** 100W, 84" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Daylight phosphor, 6500K color temperature, 76 CRI

#### Product Information

Abbrev. With Packaging Info.	F84T12DHO 15/CS 1/SKU
Actual Length (in)	81.91
Actual Length (mm)	2080.5
Average Rated Life (hr)	12000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	76
Color Temperature/CCT (K)	6500
Diameter (in)	1.59
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	6700
Mean Lumens at 25C	5427
Nominal Length (in)	84
Nominal Wattage (W)	100.00

#### Additional Product Information

[Product Documents, Graphs, and Images](#)

[Compatible Ballast](#)

[Packaging Information](#)



#### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.

[Print Page](#)

