Product Details Page 1 of 2



Product 20584

Number:

Order Abbreviation:

General

DULUX 40W long compact fluorescent lamp with 4-pin base, 3000K color temperature, 82 CRI, ECOLOGIC for use on Description:

FT40DL/830/RS/ECO

magnetic, electronic and dimming ballasts

Product Information

FT40DL830RSECO 10/CS 1/SKU Abbrev. With Packaging Info.

Average Rated Life (hr) 20000 Base 2G11 Bulb L (T5) Color Rendering Index (CRI) 82 Color Temperature/CCT (K) 3000

Family Brand Name Dulux® L

ANSI C78.901 - 2001 **Industry Standards**


2709 Mean Lumens at 25C Maximum Overall Length - MOL (in) 22.6 573 Maximum Overall Length - MOL (mm) Nominal Wattage (W) 40.00

Additional Product Information

Product Documents, Graphs, and Images

Compatible Ballast

Packaging Information



Footnotes

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- There is a NEMA supported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal end-oflife phenomenon. This end-of-life phenomenon can resultin one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMA recommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this system are yet to be defined by ANSI. For additional information refer to NEMA papers on their WEBSITE at www.NEMA.org.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified

Product Details Page 2 of 2

- conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there
- will be a corresponding increase in the average hours life.

 Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.