

[Return to search](#)[Print Page](#)

**Product Number:** 24017  
**Order Abbreviation:** FB40/D830/6  
**General Description:** 40W, T12 Curvalume rapid start fluorescent lamp, 6" leg spacing, Designer 800 rare earth phosphor, 3000K color temperature, 80 CRI

#### Product Information


Abbrev. With Packaging Info.	FB40D8306 12/CS 1/SKU
Actual Length (in)	22.6
Actual Length (mm)	574.0
Average Rated Life (hr)	18000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	80
Color Temperature/CCT (K)	3000
Diameter (in)	1.59
Diameter (mm)	40.4
Family Brand Name	Designer 800
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	3200
Mean Lumens at 25C	2880
Nominal Length (in)	22.5
Nominal Wattage (W)	40.00

#### Additional Product Information

[Product Documents, Graphs, and Images](#)

[Compatible Ballast](#)

[Packaging Information](#)



#### Footnotes

- Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.

[Print Page](#)