Page 1 of 2 **Product Details**

Return to search



Print Page

Product 29397

Number: Order

CF23EL/MINITWIST

Abbreviation:

General Description: DULUX EL 23W MiniTwist spiral compact fluorescent lamp with integral 120V ballast, medium screwbase, 3000K color

temperature, 82 CRI, packaged 6/carton

Product Information

Abbrev. With Packaging Info. CF23ELMINITWIST 6/CS 1/SKU

Average Rated Life (hr) 8000 Base Medium Bulb **MINITWIST**

Color Rendering Index (CRI) Color Temperature/CCT (K) 3000


Family Brand Name Dulux® EL

Initial Lumens at 25C 1600 Mean Lumens at 25C 1280 Maximum Overall Length - MOL (in) 5.75 120.00 Nominal Voltage (V) Nominal Wattage (W) 23.00


Additional Product Information

Product Documents, Graphs, and Images

Packaging Information



Product Details Page 2 of 2



Footnotes

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature for DULUX EL lamps is 0° F, unless otherwise specified in product literature.
- DULUX Els meet CSA, FCC and UL requirements.
- Caution: DULUX EL units cannot be used on dimming circuits (unless the lamp is labeled dimmable), emergency exit fixtures or lights, electronic timers, photocells, lighted switches or any other switches that do not meet UL20 Sec. 7.6.15. In outdoor applications, use only in enclosed fixtures to avoid exposure to weather. Use only on 120V, 60 Hz circuits. Never disassemble or modify lamp. Install or remove unit from fixture by grasping plastic base. Best performance achieved when operated at 77degrees F (25 degrees C). 40 Watt lamp is designed for base down orientation only
 The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified
 conditions and with ballast meeting ANSI specifications. If burning cycle is increased,
 there will be a corresponding increase in the average hours life.
- Minimum starting temperature for DULUX EL lamps is 0 degrees F
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.

Print Page