



Photo Controls

Relay Type Photo Controls With Adjustable Stem or Locking-Type Mounting — K100, K1200 Series

This series features "instant ON/OFF switching" in two mounting types. Complies with ANSI C136.10.



K1200



K1100



LC2000

Series K1100 – Equipped with an adjustable stem for mounting at almost any angle up to 80 degrees. Models equipped with three 6" color coded leads.

Series K1200 – Easy to install using NEMA plug-in locking type connection. Models are equipped with 2400 Volt open type spark gap arrester and standard 3-prong connector.

Size - K1100 Series – 5-3/4" (14.6 cm) High, 3" (7.6 cm) Diameter; 1/2"-14 NPT Stem;

K1200 Series – 3-3/4" (9.5 cm) High, 3" (7.6 cm) Diameter.

Activation – 1 FC "ON"; 3 - 10 FC "OFF"

Model #	Watts Tungsten	VA Ballast	Volts
K1121	1800	1800	105-130
K1122	1800	1800	210-240
K1221	1800	1800	105-130
K1222	1800	1800	210-240

** Ballast rating meets UL testing at 50% power factor.*



UL773
E59121



C22.2-55
LR38068



3/4 lbs
.34 kg



5 Year
Warranty



UL773A
E42722

Low Cost Relay Type Photo Control with Locking-Type Mounting — LC2000

Features "Instant ON/OFF Switching". Complies with ANSI C136.10

Size - 2-3/16" (5.6 cm) High, 3-3/16" (8.1 cm) Diameter

Activation – 1 to 3 FC "ON". Turn OFF to turn ON ratio is 4.

Model #	Watts Tungsten	VA Ballast	Volts
LC2000	1000	1800	110-277

Includes 110 Joule MOV Surge Arrester.



UL773
E59121



3/4 lbs
.34 kg



3 Year
Warranty