

MR-16 S-Life™ SERIES

- Accurate beam control • Crisp white light
- Available with/without cover
- Consistent light color and brightness • Extra long life - 10,000 hours

10000 Hrs

Watts	Bulb	Base	Item#	Description	Voltage (V)	ANSI	Case Qty.	CBCP (cd)	Beam Angle	Spread	Avg.Life (Hours)	Color Temp (K)	Manufacture Production Code
Extra Long Life MR16 Without Cover													
20	MR16	GU5.3	*3270	20MR16S-LIFE/SP	12	ESX	20	2400	12°	Spot	10000	2850	H02016612401
			*3271	20MR16S-LIFE/NFL	12	BBF	20	1000	24°	N.Flood	10000	2850	H02016624401
			*3272	20MR16S-LIFE/FL	12	BAB	20	400	36°	Flood	10000	2850	H02016636401
35	MR16	GU5.3	*3273	35MR16S-LIFE/SP	12	FMT	20	3200	12°	Spot	10000	2850	H03516612401
			*3274	35MR16S-LIFE/NFL	12	FMV	20	1600	24°	N.Flood	10000	2850	H03516624401
			*3275	35MR16S-LIFE/FL	12	FMW	20	900	36°	Flood	10000	2850	H03516636401
50	MR16	GU5.3	*3276	50MR16S-LIFE/SP	12	EXT	20	5500	12°	Spot	10000	2850	H05016612401
			*3277	50MR16S-LIFE/NFL	12	EXZ	20	2500	24°	N.Flood	10000	2850	H05016624401
			*3278	50MR16S-LIFE/FL	12	EXN	20	1400	36°	Flood	10000	2850	H05016636401
			*3279	50MR16S-LIFE/WFL	12	FNV	20	700	60°	W.Flood	10000	2850	H05016660401
75	MR16	GU5.3	*3280	75MR16S-LIFE/SP	12	EYF	20	6000	12°	Spot	10000	2850	H07516612401
			*3281	75MR16S-LIFE/NFL	12	EYJ	20	2500	24°	N.Flood	10000	2850	H07516624401
			*3282	75MR16S-LIFE/FL	12	EYC	20	1400	36°	Flood	10000	2850	H07516636401
Extra Long Life MR16 With Cover													
20	MR16	GU5.3	*3283	20MR16S-LIFE/SP/C	12	ESX	20	2300	12°	Spot	10000	2850	H02016612501
			*3284	20MR16S-LIFE/NFL/C	12	BBF	20	900	24°	N.Flood	10000	2850	H02016624501
			3251	20MR16S-LIFE/FL/C	12	BAB	20	360	36°	Flood	10000	2850	H02016636501
35	MR16	GU5.3	*3285	35MR16S-LIFE/SP/C	12	FMT	20	3000	12°	Spot	10000	2850	H03516612501
			*3286	35MR16S-LIFE/NFL/C	12	FMV	20	1200	24°	N.Flood	10000	2850	H03516624501
			3252	35MR16S-LIFE/FL/C	12	FMW	20	900	36°	Flood	10000	2850	H03516636501
50	MR16	GU5.3	*3287	50MR16S-LIFE/SP/C	12	EXT	20	5000	12°	Spot	10000	2850	H05016612501
			*3288	50MR16S-LIFE/NFL/C	12	EXZ	20	2400	24°	N.Flood	10000	2850	H05016624501
			3253	50MR16S-LIFE/FL/C	12	EXN	20	1300	36°	Flood	10000	2850	H05016636501
			*3289	50MR16S-LIFE/WFL/C	12	FNV	20	600	60°	W.Flood	10000	2850	H05016660501
75	MR16	GU5.3	*3290	75MR16S-LIFE/SP/C	12	EYF	20	5800	12°	Spot	10000	2850	H07516612501
			*3291	75MR16S-LIFE/NFL/C	12	EYJ	20	2400	24°	N.Flood	10000	2850	H07516624501
			*3292	75MR16S-LIFE/FL/C	12	EYC	20	1300	36°	Flood	10000	2850	H07516636501

* Items only available for special orders

All measurements are shown in inches unless noted

