



MR-16 SERIES

- Accurate beam control • Crisp white light
- Available with/without cover
- Consistent light color and brightness

Watts	Bulb	Base	Item#	Description	Voltage (V)	ANSI	Case Qty.	CBCP (cd)	Beam Angle	Spread	Avg.Life (Hours)	Color Temp (K)	Manufacture Production Code
Standard MR16 Without Cover													
20	MR16	GU5.3	3212	20MR16/SP	12	ESX	20	3500	12°	Spot	2000	2950	H02016612001
			3213	20MR16/NFL	12	BBF	20	1200	24°	N.Flood	2000	2950	H02016624001
			3214	20MR16/FL	12	BAB	20	600	36°	Flood	2000	2950	H02016636001
35	MR16	GU5.3	3215	35MR16/SP	12	FMT	20	6000	12°	Spot	2000	2950	H03516612001
			3216	35MR16/NFL	12	FMV	20	2300	24°	N.Flood	2000	2950	H03516624001
			3217	35MR16/FL	12	FMW	20	1300	36°	Flood	2000	2950	H03516636001
50	MR16	GU5.3	3218	50MR16/SP	12	EXT	20	11000	12°	Spot	2000	3000	H05016612001
			3219	50MR16/NFL	12	EXZ	20	3600	24°	N.Flood	2000	3000	H05016624001
			3220	50MR16/FL	12	EXN	20	2000	36°	Flood	2000	3000	H05016636001
			*3263	50MR16/WFL	12	FNV	20	850	60°	W.Flood	2000	3000	H05016660001
75	MR16	GU5.3	3221	75MR16/SP	12	EYF	20	13000	12°	Spot	2000	3000	H07516612001
			3222	75MR16/NFL	12	EYJ	20	4800	24°	N.Flood	2000	3000	H07516624001
			3223	75MR16/FL	12	EYC	20	2700	36°	Flood	2000	3000	H07516636001
Standard MR16 With Cover													
20	MR16	GU5.3	3224	20MR16/SP/C	12	ESX	20	3500	12°	Spot	2000	2950	H02016612101
			3225	20MR16/NFL/C	12	BBF	20	1200	24°	N.Flood	2000	2950	H02016624101
			3226	20MR16/FL/C	12	BAB	20	600	36°	Flood	2000	2950	H02016636101
35	MR16	GU5.3	3227	35MR16/SP/C	12	FMT	20	6000	12°	Spot	2000	2950	H03516612101
			3228	35MR16/NFL/C	12	FMV	20	2300	24°	N.Flood	2000	2950	H03516624101
			3229	35MR16/FL/C	12	FMW	20	1300	36°	Flood	2000	2950	H03516636101
50	MR16	GU5.3	3230	50MR16/SP/C	12	EXT	20	11000	12°	Spot	2000	3000	H05016612101
			3231	50MR16/NFL/C	12	EXZ	20	3600	24°	N.Flood	2000	3000	H05016624101
			3232	50MR16/FL/C	12	EXN	20	2000	36°	Flood	2000	3000	H05016636101
			*3264	50MR16/WFL/C	12	FNV	20	850	60°	W.Flood	2000	3000	H05016660101
75	MR16	GU5.3	3233	75MR16/SP/C	12	EYF	20	13000	12°	Spot	2000	3000	H07516612101
			3265	75MR16/NFL/C	12	EYJ	20	4800	24°	N.Flood	2000	3000	H07516624101
			3234	75MR16/FL/C	12	EYC	20	2700	36°	Flood	2000	3000	H07516636101

* Items only available for special orders

All measurements are shown in inches unless noted



MR16/GU5.3



GU5.3