

[Return to search](#)

[Print Page](#)



Product Number: 58838
Order Abbreviation: 20MR16/IR/WFL60/C 12V
General Description: ENERGY SAVING, LOW VOLTAGE, 20 WATT WIDE FLOOD MR16. 12 VOLTS. DICHROIC REFLECTOR PASSES HEAT OUT OF THE BACK OF THE BULB

Product Information

Abbrev. With Packaging Info.	20MR16IRWFL60C 12V 20/CS 1/SKU
Average Rated Life (hr)	5000
Base	GU5.3 Bipin
Beam Angle (deg)	60
Beam Type	WFL
Bulb	MR16
Centerbeam Candlepower (cp)	450
Class	C (gas)
Diameter (in)	2
Diameter (mm)	50.8
Ecologic	YES
Filament	AXIAL
Horizontal Beam Angle (deg)	60
Lamp Finish	Reflector
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	44.45
Nominal Voltage (V)	12.00
Nominal Wattage (W)	20.00
Vertical Beam Angle (deg)	60

Additional Product Information

[Product Documents, Graphs, and Images](#)

[Packaging Information](#)



Footnotes

- Infrared lamp technology
- Max. seal temperature 370 C (662F)

- UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector and infrared reflective coating on the lamp capsule.
- Max pin temperature 220 C.
- Max temperature at lens reflector joint 240 C.

[Print Page](#)