

[Return to search](#)

[Print Page](#)



**Product Number:** 58634  
**Order Abbreviation:** 37MR16/IR/NFL25/C 12V  
**General Description:** Tungsten Halogen Tru-Aim MR16 IR UV-Stop Capsule With Axial Filament, Hard Dichroic Reflector GU5.3 Bi-Pin Base 37W 12Volt Narrow Flood Beam

**Product Information**

Abbrev. With Packaging Info.	37MR16IRNFL25C12V 20/CS 1/SKU
Average Rated Life (hr)	5000
Base	GU5.3 Bipin
Beam Angle (deg)	25
Beam Type	NFL
Bulb	MR16
Centerbeam Candlepower (cp)	4400
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	2
Diameter (mm)	50.8
Ecologic	YES
Family Brand Name	TRU-AIM® IR
Filament	AXIAL
Horizontal Beam Angle (deg)	25
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	44.45
Nominal Voltage (V)	12.00
Nominal Wattage (W)	37.00
Vertical Beam Angle (deg)	25

**Additional Product Information**

[Product Documents, Graphs, and Images](#)

[Packaging Information](#)



**Footnotes**

- UV Filter capsule with axial filament in constant color, hard coated Dichroic reflector and infrared reflective coating on the lamp capsule.
- Infrared lamp technology
- Max. seal temperature 370 C (662F)
- Max pin temperature 250 C.
- Max temperature at lens reflector joint 240 C.

**| Print Page |**