

JDR & JCDR SERIES


Only for Use in Approved Halogen Fixtures
 Average Life 2,000 Hours
 Operate Base Up

Watts	Item code	Description	Voltage (V)	Base	CBCP (cd)	Dimension		Beam Angle	Approx Lumens (lm)	Avg. Life (Hours)	Color Temp (K)	Case Qty.
						Dia (in)	MOL (in)					
JDR Series - With Cover												
*35	H03514340302	JDR35/E14	120V	E14	700	2.00	2.90	40°	320	2000	3000	10
*50	H05014340302	JDR50/E14	120V	E14	1200	2.00	2.90	40°	590	2000	3000	10
*75	H07514340302	JDR75/E14	120V	E14	1300	2.00	2.90	40°	990	2000	3000	10
*35	H03527340302	JDR35/E26	120V	E26	700	2.00	3.00	40°	320	2000	3000	10
50	H05027340302	JDR50/E26	120V	E26	1200	2.00	3.00	40°	590	2000	3000	10
75	H07527340302	JDR75/E26	120V	E26	1300	2.00	3.00	40°	990	2000	3000	10
35	H03510325302	JDR35/FL/GU10	120V	GU10	1800	2.00	2.10	25°	320	2000	3000	20
35	H03510350302	JDR35/WFL/GU10	120V	GU10	1800	2.00	2.10	50°	320	2000	3000	20
50	H05010325302	JDR50/FL/GU10	120V	GU10	1800	2.00	2.10	25°	590	2000	3000	20
50	H05010350302	JDR50/WFL/GU10	120V	GU10	1800	2.00	2.10	50°	590	2000	3000	20
75	H07510325302	JDR75/FL/GU10	120V	GU10	1800	2.00	2.10	25°	990	2000	3000	20
75	H07510350302	JDR75/WFL/GU10	120V	GU10	1800	2.00	2.10	50°	990	2000	3000	20
JCDR Series - With Cover												
50	H05054383002	JCDR50	120V	G5.3	1200	2.00	1.78	38°	980	2000	3000	20
*75	H07554383002	JCDR75	120V	G5.3	1300	2.00	1.78	38°	1500	2000	3000	20
*100	H10054383002	JCDR100	120V	G5.3	2800	2.00	1.78	38°	2000	2000	3000	20


TUNGSTEN HALOGEN LAMPS

* Items only available for special orders


All measurements are shown in inches unless noted




E14 Base



E26 Base



GU10 Base



G5.3 Base