

[Return to search](#)

[Print Page](#)



Product Number: 58325
Order Abbreviation: 50MR16/SP10/C(EXT) 12V
General Description: Tungsten Halogen Tru-Aim MR16 STANDARD Axial Filament Dichroic Reflector Cover Glass GU5.3 Bi-Pin Base 50Watt 12Volt Spot Beam


Product Information

Abbrev. With Packaging Info.	50MR16SP10CEXT 12V 20/CS 1/SKU
ANSI Code	EXT
Average Rated Life (hr)	2000
Base	GU5.3 Bipin
Beam Angle (deg)	10
Beam Type	SP
Bulb	MR16
Centerbeam Candlepower (cp)	7800
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	2
Diameter (mm)	50.8
Ecologic	YES
Family Brand Name	TRU-AIM Standard
Filament	AXIAL
Horizontal Beam Angle (deg)	10
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	45.0
Nominal Voltage (V)	12.00
Nominal Wattage (W)	50.00
Vertical Beam Angle (deg)	10

Additional Product Information

[Product Documents, Graphs, and Images](#)

[Packaging Information](#)



**Footnotes**

- UV Filter capsul with axial filament in covered dichroic reflector.
- Max. seal temperature 370 C (662F)
- Max pin temperature 250 C.
- Max temperature at lens reflector joint 240 C.
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.

[Print Page](#)