

# Spring Wound Timers



## Spring Wound Timers Commercial Grade and Decor Style

Energy Saving Timers that require no electricity to operate.

Commercial Grade Aluminum Wall plate	Decor Series White Wall plate
<b>PM-15M</b> - 15 minutes on	<b>PD-15M</b> - 15 minutes on
<b>PM-30M</b> - 30 minutes on	<b>PD-30M</b> - 12 minutes on
<b>PM-60M</b> - 60 minutes on	<b>PD-60M</b> - 60 minutes on
<b>PM-12H</b> - 12 hours on	<b>PD-12H</b> - 12 hours on

Specifications	
<b>SPST Switch Contact Rating (50/60 HZ)</b>	
20A@125VAC (Resistive / Inductive)	
1HP@125VAC (Inductive)	
7A@125VAC (Tungsten)	
10A@250VAC (Resistive / Inductive)	
10A@277VAC (Resistive / Inductive)	
<b>Wiring Connections:</b>	Screw Terminals
<b>Operating Temperatures:</b>	-20°F to 185°F
N.O. and N.C. Terminals	

## Multifunction Digital In Wall Timer

- 1 Timer replaces 6
- Time intervals in 5, 10, 15 & 30 min. or 1, 2 & 4 hour durations
- 100% compatible with CFL and LED
- 120 V / 60 Hz / SPST
- Rated 800 watts resistive
- UL listed
- Model DT-124 with white wall plate

