

Spring Wound Timers



Spring Wound Timers Commercial Grade and Decor Style

Energy Saving Timers that require no electricity to operate.

Commercial Grade Aluminum Wall plate	Decor Series White Wall plate
PM-15M - 15 minutes on	PD-15M - 15 minutes on
PM-30M - 30 minutes on	PD-30M - 12 minutes on
PM-60M - 60 minutes on	PD-60M - 60 minutes on
PM-12H - 12 hours on	PD-12H - 12 hours on

Specifications	
SPST Switch Contact Rating (50/60 HZ)	
20A@125VAC (Resistive / Inductive)	
1HP@125VAC (Inductive)	
7A@125VAC (Tungsten)	
10A@250VAC (Resistive / Inductive)	
10A@277VAC (Resistive / Inductive)	
Wiring Connections:	Screw Terminals
Operating Temperatures:	-20°F to 185°F
N.O. and N.C. Terminals	

Multifunction Digital In Wall Timer

- 1 Timer replaces 6
- Time intervals in 5, 10, 15 & 30 min. or 1, 2 & 4 hour durations
- 100% compatible with CFL and LED
- 120 V / 60 Hz / SPST
- Rated 800 watts resistive
- UL listed
- Model DT-124 with white wall plate

