

ISB SOLA BASIC



REV: "A"

FLUORESCENT BALLAST SPECIFICATIONS


DESCRIPTION

CATALOG E450-F-160-TP	TYPE Energy efficient magnetic	STARTING METHOD Instant Start	NUMBER OF LAMPS 1	LAMP TYPE F96SST12, F96T12, F72T12
---------------------------------	-----------------------------------	----------------------------------	----------------------	---------------------------------------

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE 120v	LAMP WATTS 60/75/55w	INPUT WATTS 101w	INPUT CURRENT 0.90 A	OCV 620v	PF 0.94	FREQUENCY 60 Hz	SOUND RATED B
MIN START TEMP 0°F (60°F/SS lamp)	CLASS P	TYPE 1 outdoor	BALLAST FACTOR 0.93 (0.93 / SS lamp)	BEF 0.92	THD 26%	NO PCB'S	

PHYSICAL CHARACTERISTICS




CASE DIMENSIONS							
UNITS	M1	M2	M3	W	L	H	
INCHES	2.0	11.140	10.5	3.109	11.750	1.781	
TOL(+/-)	0.010	0.010	0.010	0.050	0.050	0.050	
MM	51	283	267	79	298	45	
TOL(+/-)	0.25	0.25	0.25	1.30	1.30	1.30	
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	YELLOW		
INCHES	8	48		48			
TOL(+/-)	3/8	3/8		3/8			
MM	203	1219		1219			
TOL(+/-)	10	10		10			

CARTON CHARACTERISTICS


UNITS/CARTON 6	CARTONS/LAYER 12	# OF LAYERS 4	UNITS/PALLET 288	PIECE WEIGHT 8 lbs	CARTON WEIGHT 49 lbs	PALLET WEIGHT 2,391 lbs
CARTONS/PALLET 48	CARTON DIMENSIONS 12" x 12" x 4"		PALLET DIMENSIONS 40" x 48" x 7"	PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40" x 48" x 24"		

CARTON LABEL

ELECTRICAL DIAGRAM



PRODUCT LABEL



SOLA

120 VOLT 0.99 AMP 620 OCV 60 HZ HIGH POWER FACTOR INSTANT START BALLAST

E450-F-160-TP

GROUND BALLAST CASE CLASS P

FOR: 1-F96T12/IS or 1-F72T12/IS at 15.5° C Min. max.: 1-F96T12/IS/ES

MINIMUM -18° C MADE IN MEXICO

3 YEAR WARRANTY

NON PCB

CLASS P AUTOMATIC RESETTING THERMAL PROTECTOR TYPE 1 OUTDOOR

OUTPUT LAMP/PILES

UL LISTED 5 P 49

SP LR 106489

ISO 9001

Barcode: 5 6100774201116

Lighting and Power Source
2707 Realty Road, Suite 110
Carrollton, TX 75006
Tel: (888) 385-4448
Fax: (972) 418-5858