




Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 72279**72279 – GE254MVPS-D**

GE LFL UltraStart® Electronic Program / Rapid Start Ballast




- High Efficiency T5 ballast with Continuous Cathode Cutout Technology
- Lower Maintenance Costs with Parallel Lamp Operation
- Fast Starting Time <700ms
- Multi-Voltage technology means a single ballast handles voltage from 108V to 305V
- Auto-Restart withstands temporary losses in power without the need to cycle power
- Anti-Striation Control for better light quality, with no striations.
- Cold temperature -20F Minimum Starting Temperature

[View Larger](#)**GENERAL CHARACTERISTICS**

Application	2 or 1 - F54T5HO 120 to 277 UltraStart PRS D Can
Category	Linear Fluorescent
Ballast Type	Electronic - Program / Rapid Start
Starting Method	Programmed start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10 %
Case Temperature (MAX)	70 °C (158 °F)
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal
Additional Info	Auto-restart, End of Life Protection (EOL), Thermally protected, Universal voltage

DIMENSIONS

Case dimensions	
Length (L)	16.7 in (424.18 mm)
Width (W)	1.2 in (29.97 mm)
Height (H)	1.0 in (25.40 mm)
Mounting dimensions	
Mount Length (M)	16.4 in (417.32 mm)
Weight	1.85 lbs
Exit Type	Side
Remote mounting distance to lamp	8 ft
Remote Mounting Wire Gauge	18 AWG

[View Larger](#)**ELECTRICAL CHARACTERISTICS**

Supply Current Frequency	50 Hz/60 Hz
--------------------------	-------------

PRODUCT INFORMATION





Product Code	72279
Description	GE254MVPS-D
Standard Package	Case
Standard Package GTIN	10043168722794
Standard Package Quantity	10

Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168722797

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor % (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/C)	
FT55W/4P	1	120	70	0.59 A	1.04	1.49	99	1.6	7	-20.0 / -29	System specs
	1	277	69	0.25 A	1.04	1.51	97	1.6	11	-20.0 / -29	System specs
FT55W/4P	2	277	107	0.39 A	0.86	0.80	98	1.7	8	-20.0 / -29	System specs
FT55W/4P	2	120	107	0.90 A	0.86	0.80	99	1.7	7	-20.0 / -29	System specs
FT50W/4P	1	120	76	0.64 A	1.20	1.58	99	1.6	7	-20.0 / -29	System specs
	1	277	75	0.28 A	1.21	1.61	97	1.6	10	-20.0 / -29	System specs
FT50W/4P	2	120	123	1.03 A	1.05	0.85	99	1.7	7	-20.0 / -29	System specs
FT50W/4P	2	277	116	0.43 A	1.06	0.91	99	1.7	8	-20.0 / -29	System specs
FT36W/4P	1	120									
	1	277									
	2	120									
	2	277									
F58T8	1	120	69	0.58 A	1.09	1.58	99	1.6	7	-20.0 / -29	System specs
	1	277	69	0.25 A	1.09	1.58	97	1.6	11	-20.0 / -29	System specs
	2	120	108	0.91 A	0.95	0.88	99	1.6	7	-20.0 / -29	System specs
	2	277	105	0.38 A	0.95	0.90	98	1.6	8	-20.0 / -29	System specs
F54T5/WM	2	120	112	0.94 A	1.00	0.89	99	1.7	5	0.0 / -18	System specs
	2	277	111	0.41 A	1.00	0.90	98	1.7	8	0.0 / -18	System specs
	1	120	71	0.59 A	1.13	1.59	99	1.5	6	0.0 / -18	System specs
	1	277	71	0.26 A	1.13	1.59	98	1.5	8	0.0 / -18	System specs
F54T5/HO	1	120	76	0.64 A	1.11	1.46	99	1.5	6	-20.0 / -29	System specs
	1	277	75	0.28 A	1.12	1.49	98	1.7	8	-20.0 / -29	System specs
	2	120	119	0.99 A	1.00	0.84	99	1.7	5	-20.0 / -29	System specs
	2	277	117	0.43 A	1.00	0.85	98	1.7	7.9	-20.0 / -29	System specs


Safety & Performance

- RoHs Compliant
-  UL Type 1 Outdoor
Meets ANSI Standard C82.11-Cons 2002
-  UL Type HL
FCC - CLASS A Non-Consumer
-  UL Class P
-  UL Type CC

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.

[Download full warranty](#)



Meets ANSI Standard C62.41-1991



ADDITIONAL RESOURCES

[Catalogs](#)

[Testimonials](#)

Brochures

Product Brochures

- [71884_UltraStartWattMiserT5SystemBrochure.pdf](#)
- [71885_T5WattMiserHighOutput.pdf](#)
- [UltraStart T5 ProgStartBallastBrochure-72757.pdf](#)

[Disposal Policies & Recycling Information](#)

[Return To Top](#)

Photos are representational only. Sizes, shapes and labels of ballast may vary.

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2009