Home | Language | Find a Representative | Contact Us



CustomerService | Ballasts / Transformers | Lamps | Custom Products | Company



LH2-277-L

FLUORESCENT REMOTE MOUNT ELECTRONIC BALLAST

6 BALLASTS OPERATE 124 LAMPS IN 628 COMBINATIONS

· Solid-State Electronics · High Power Factor · Lightweight

. Operates up to 20 feet from Lamp . Versatile . Energy Saving

Ballast Specifications

Maximum Power: 35W Model Number: LH2-277-L Maximum Current: .15 AMP

Operating Voltage: 277 VAC

Product Photo: click here to view

Case Specifications

Black/White Wires: 18" Red/Yellow Wires: 36"

Ballast Case Size: H 1.25" x W 1.72" x L

Ballast Weight: 14 oz.

Case Quantity: 50 pcs.

Case Weight: 44 lbs.

Specifications Common to all LongHorse Ballasts

Frequency: 50/60 Hz

ATHD: Meets ANSI C82.11-1993

Protection/Output: Open Lamp Shortened

Lamp

Protection/Overcurrent: Fuse

Protection/Voltage Transients: MOV (PER

ANSI C82.11 - 1993)

EMI/RFI: FCC PART 18-A

Regulatory Approvals: UL & cUL Listed Type 1

Outdoors

High Power Factor: >.90

Open Circuit Voltage: 600 V RMS Max. Min. Operating Temp.: -20* F (-30* C)

Max. Case Temp.: 158* F (70* C)

Lamp Starting Mode: Instant Start

Class P: Thermal Sound Rating: A