Home | Language | Find a Representative | Contact Us



CustomerService | Ballasts / Transformers | Lamps | Custom Products | Company



## FLUORESCENT REMOTE MOUNT ELECTRONIC BALLAST

**Case Specifications** 

6 BALLASTS OPERATE 124 LAMPS IN 628 COMBINATIONS

· Solid-State Electronics · High Power Factor · Lightweight

. Operates up to 20 feet from Lamp . Versatile . Energy Saving

**Ballast Specifications** 

ANSI C82.11 - 1993)

Maximum Power: 70W Black/White Wires: 18" Model Number: LH4-277-L Red/Yellow Wires: 36"

Maximum Current: .22 AMP Ballast Case Size: H 1" x W 1.72" x L 9.5"

Operating Voltage: 277 VAC Ballast Weight: 14 oz. Product Photo: click here to view Case Quantity: 50 pcs.

Case Weight: 44 lbs.

## **Specifications Common to all LongHorse Ballasts**

Frequency: 50/60 Hz Regulatory Approvals: UL & cUL Listed Type 1

Outdoors ATHD: Meets ANSI C82.11-1993

High Power Factor: >.90 Protection/Output: Open Lamp Shortened

Open Circuit Voltage: 600 V RMS Max.

Protection/Overcurrent: Fuse Min. Operating Temp.: -20\* F (-30\* C)

Protection/Voltage Transients: MOV (PER Max. Case Temp.: 158\* F (70\* C)

Lamp Starting Mode: Instant Start EMI/RFI: FCC PART 18-A

Class P: Thermal

Sound Rating: A