

2110 SERIES

1/2" CONDUIT MOUNTING DIE CAST ALUMINUM PHOTOCONTROL



APPLICATIONS

- Parking lot lighting
- Building perimeter lighting
- Outdoor signage



FEATURES

SENSOR: Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.

STANDARDS: Meets ANSI/UL773A.

OPERATION: Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.

HOUSING: Die cast aluminum housing and base. Gasketed for weather protection.

ENERGY SAVINGS: Works with screw base CFLs.

SPECIFICATIONS

ON/OFF: Turn ON is 1 to 5fc, Turn OFF is 3 to 15fc, without the slide in position. ON/OFF adjustment is easily made by moving a slide cover. No tools required.

TIME DELAY: ON and OFF.

CELL: Cadmium sulphide, epoxy conformal coated 1/2" diameter. MODEL 2117 is 1" cell.

CONTACTS: Remain closed between dusk and dawn (the unit fails in the ON position).

LEAD WIRES: Three color coded, minimum 6" wire leads, #16AWG, rated for 105 °C. (2117 #10AWG red and black).

POWER CONSUMPTION:

Averages under 1 watt.

TEMPERATURE RANGE:

-40 °F to +140 °F (-40 °C to +60 °C).

FAIL MODE: ON.

WARRANTY: 5 years.

| CAT. NO. | UPC CODE | VOLTAGE (VAC) 50-60Hz | RATING | | LED |
|----------|----------|-----------------------|------------|-------------|-------------|
| | | | TUNGSTEN | BALLAST | |
| 2115 | 60032 | 120 | 2000W | 1800VA | 600VA |
| 2116 | 60033 | 208-277 | 3470-4620W | 2080-2770VA | 1040-1385VA |
| 2117* | 60037 | 120 | 3000W | 3000VA | - |
| 73866 | 62020 | Mounting Bracket | - | - | - |

*Not UL or CSA rated.

