

HALOGEN LOW VOLTAGE BI-PIN

Watts	Ushio Ordering Code	Ushio Lamp Code	Dimensions mm			Filament Type	Approx Lumens lm	Color Temp K	Avg Life h	Burn Position	Bulb Finish	Fig No
			Dia (A)	OAL (B)	LCL (C)							
20	1000822	JC12V-20W	11.0	44.0	30.0	C-6	280	2850	2000	Any	Clear	1
35	1000823	JC12V-35W	11.0	44.0	30.0	C-6	650	2900	2000	Any	Clear	1
50	1000830	JC12V-50WG1.0	11.0	44.0	30.0	C-6	900	2900	2000	Any	Clear	1
50	1000848	JC24V-50W	10.5	44.0	30.0	C-6	750	2950	2000	Any	Clear	1
75	1000849	JC24V-75W	10.5	44.0	—	CC-8	—	—	—	Any	Clear	2
150	1000492	FCS, JC24V-150WUI	13.5	50.0	32.0	CBar6	5000	—	50	BD/Hor	Clear	1
150	1000537	FHY, JC24V-150W	13.5	50.0	30.0	CBar6	3700	3100	1000	BD/Hor	Clear	1
250	1000382	EVC/FGX, JC24V-250W	13.0	64.0	35.0	CBar6	8400	3400	300	Any	Clear	1
400	1000383	EVD, JC36V-400WS1	16.0	60.0	36.0	CBar6	14500	3450	50	BD/Hor	Clear	1
150	1000843	JC24V-150WL-H	13.5	61.0	37.0	CBar6	4800	3400	50	BD/Hor	Clear	3

