



DuraMax 75W 120V R20 FR TP 1 CT

Product family description

Philips DuraMax® Long Life Reflector Flood Bulbs reduce the hassle of replacing light bulbs every few months, since all DuraMax products last longer than standard incandescent light bulbs. Available in a variety of sizes and wattages. Use flood lights for general or ambient lighting; use spot lights to highlight artwork or architecture. Both are ideal for use in recessed cans or track lighting fixtures.

Features

- Lasts at Least One and a Half Years!
- Medium base.
- Available in a variety of wattages.
- Available in flood version for general or ambient lighting; Available in spot version to highlight artwork or architecture.
- Available in R20: 30, 50 and 75 watt; Br30 Flood: 45, 65, and 85 watt; BR30 Spot: 65 and 85 watt; BR40 Flood: 65, 85 and 120 watt; BR40 Spot: 120 watt.
- * Based on an average of hours usage per day/7 days per week. Hours differ between products, and there are exceptions. See individual products for details.

Application

- The DuraMax flood reflectors are ideal for general or ambient lighting in recessed cans or track lighting fixtures. The DuraMax Spot reflector highlights artwork and architecture.

Notes

- Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.

Footnotes

- Effective on 1/1/07, this lamp is not for sale in the states of Washington and Oregon.(907)

PHILIPS

- Effective on 1/1/08, this lamp is not for sale in the states of Washington, Oregon, California, Vermont, Rhode Island, and Massachusetts. (910)

| Product data | |
|--------------------------------|--------------------------------------|
| Product Number | 167635 |
| Full product name | DuraMax 75W 120V R20 FR TP ICT |
| Ordering Code | 75R20/LL 120V TP |
| Pack type | 1 Lamp in a Folding Carton |
| Pieces per Sku | 1 |
| Skus/Case | 12 |
| Pack UPC | 046677167639 |
| EAN2US | |
| Case Bar Code | 50046677167634 |
| Successor Product number | |
| Base | Medium [Single Contact Medium Screw] |
| Base Information | Aluminum [Aluminum Base] |
| Bulb | R-20 |
| Bulb Finish | Frosted |
| Filament Shape | CC6 [Straight] |
| Operating Position | Universal [Any or Universal (U)] |
| Packing Type | ICT [1 Lamp in a Folding Carton] |
| Packing Configuration | 12 |
| Atmosphere | Gas |
| RatedAvgLife(See Family Notes) | 2500 hr |
| Ordering Code | 75R20/LL 120V TP |
| Pack UPC | 046677167639 |
| Case Bar Code | 50046677167634 |
| Watts | 75W |
| Voltage | 120V |
| Initial Lumens | 570 Lm |
| Max Overall Length (MOL) - C | 3.94 in |
| Special packing | TP [Tray Pack] |
| Product Number | 167635 |



©2009 Koninklijke Philips Electronics N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Document order number : 0000 000 00000