



Locking-Type Mounting, Thermal Type — K4500 Series

Easy to install; just plug in and twist. This series is equipped with standard 3-prong NEMA locking-type plug connections. Incorporates K4000 style thermal switch for reliable long life performance. Complies with ANSI C136.10.

Size – 3-3/4" (9.5 cm) High, 3" (7.6 cm) Diameter.

| Model # | Watts Tungsten | VA Ballast | Amps Tungsten | Amps Ballast | Volts |
|---------|----------------|------------|---------------|--------------|-------|
| K4521 | 1800 | 1000 | 15 | 8.3 | 120 |
| K4524** | 3100 | 1700 | 15 | 8.3 | 208 |
| K4522 | 3600 | 2000 | 15 | 8.3 | 240 |
| K4533** | 4100 | 2300 | 15 | 8.3 | 277 |
| K4535** | 7200 | 4000 | 15 | 8.3 | 480 |

* Ballast rating meets UL testing at 50% power factor.

** Not CSA certified.



UL773
E59121



C22.2-177
LR38068



3/4 lbs
.34 kg



5 Year
Warranty

Accessories for Locking-Type Controls

Pole Bracket Adapter – Model K122 - 105 to 480 Volts; for use with K1200, K4500 or LC4500 Series locking-type controls. K121 – receptacle only, K121-30 receptacle with 30 inch leads.

Shorting Cap – Model K4500 - 105 to 480 Volts; replaces locking-type photo control to complete circuit.



Low Cost Locking-Type, Thermal Type — LC4500 Series

The LC4500 Series provides low cost reliable control for street lighting and other applications requiring a NEMA twist and lock type plug connection. An integral housing and lens, with UV protection, keeps moisture out and ensures long life. Complies with ANSI C136.10.

Activation – .5 FC minimum "ON"; 15 FC maximum "OFF".

Size – 2-3/4" (7.0 cm) High, 3" (7.6 cm.) Diameter.

Color – Translucent with color coded band for voltage identification.

| Model # | Watts Tungsten | VA Ballast | Volts |
|------------|----------------|------------|----------------|
| LC4521C | 1000 | 1000 | 120 |
| LC4523 | 1700-2300 | 1700-2300 | 208-277 |
| LC4527 | 5205 | 2880 | 347 |
| LC4535** | 7200 | 4000 | 480 |
| LC4536C | 1000-2300 | 1000-2300 | 120 or 208-277 |
| LC4521LA | 1000 | 1000 | 120 |
| LC4523LA | 1700-2300 | 1700-2300 | 208-277 |
| LC4535LA** | 7200 | 4000 | 480 |
| LC4536LAC | 1000-2300 | 1000-2300 | 120 or 208-277 |

LA Models equipped with 2400 volt open type spark gap arrester.

* Ballast rating meets UL testing at 50% power factor.

** Not CSA certified.



UL773
E59121



C22.2-55
LR38068



2 lbs
.09 kg



3 Year
Warranty



K4521



K122



K4500



K121
K121-30



LC4521C