



**Product Number:** 64599

**Order Abbreviation:** MP150PAR38/U/VWFL65/ECO

**General Description:** 150W open fixture rated metal halide lamp, clear, very wide flood, universal burn

Product Information	
Abbrev. With Packaging Info.	MP150PAR38UVWFL65ECO 6/CS 1/SKU
ANSI Code	M102/O
Approx. Lumens (initial - horizontal)	8800
Approx. Lumens (initial - vertical)	8800
Average Rated Life - Horizontal (hr)	8500
Average Rated Life - (hr)	8500
Average Rated Life - Vertical (hr)	8500
Base	E26 Medium
Beam Angle (deg)	65
Beam Type	VWFL
Bulb	PAR38
Centerbeam Candlepower (cp)	7500
Color Rendering Index (CRI)	75
Color Temperature/CCT (K)	3200
Diameter (in)	4.764
Diameter (mm)	121.00
Family Brand Name	Metalarc Pro-Tech® Par38/ECO
Fixture Requirement	O
Hot Restrike Time (min)	5-7
Maximum Base Temperature - Fahrenheit	374
Maximum Base Temperature - Celsius	190
Maximum Bulb Temperature - Fahrenheit	662
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.32
Maximum Overall Length - MOL (mm)	135
Nominal Voltage (V)	95.00
Nominal Wattage (W)	150.00
Operating Position	Universal
Warm-up Time (min)	2-4



**Footnotes**

- Use with 4000V pulse rated sockets only.
- Passes Federal TCLP test based on NEMA LL Series Standards. TCLP data available upon request. Disposal regulations may vary depending on location. Please check your local and state/provincial regulations.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaires. See lamp warning.
- Lamps with a E26 medium skirt base are not compatible with exclusionary medium sockets.