



DULUX® D

DULUX® T

### DULUX® D/E 4-PIN ECOLOGIC® COMPACT FLUORESCENT LAMPS

for Dimming and Electronic Ballast. Lamps have End-of-lamp Life (EOL) Protection

Nominal Wattage	Bulb	MOL		Base	Product Number	Ordering Abbreviation	NEMA Generic Designation	Pkg Qty	Avg Rated Life (hrs)	CCT (K)	CRI	Approx Lumens @25°C/77°F		Symbols & Footnotes
		(in)	(mm)									Initial	Mean	
13	D (T4)	5.2	131	G24Q-1	20682	CF13DD/E/827/ECO	CFQ13W/G24Q/827	50	12000	2700	82	900	774	1,2,5,6, 7,12,20
					20721	CF13DD/E/830/ECO	CFQ13W/G24Q/830	50	12000	3000	82	900	774	1,2,5,6, 7,12,20
					20671	CF13DD/E/835/ECO	CFQ13W/G24Q/835	50	12000	3500	82	900	774	1,2,5,6, 7,12,20
					20667	CF13DD/E/841/ECO	CFQ13W/G24Q/841	50	12000	4100	82	900	774	1,2,5,6, 7,12,20
18	D (T4)	5.8	147	G24Q-2	20683	CF18DD/E/827/ECO	CFQ18W/G24Q/827	50	12000	2700	82	1150	989	1,2,5,6, 7,12,20
					20724	CF18DD/E/830/ECO	CFQ18W/G24Q/830	50	12000	3000	82	1150	989	1,2,5,6, 7,12,20
					20672	CF18DD/E/835/ECO	CFQ18W/G24Q/835	50	12000	3500	82	1150	989	1,2,5,6, 7,12,20
					20668	CF18DD/E/841/ECO	CFQ18W/G24Q/841	50	12000	4100	82	1150	989	1,2,5,6, 7,12,20
26	D (T4)	6.5	166	G24Q-3	20684	CF26DD/E/827/ECO	CFQ26W/G24Q/827	50	12000	2700	82	1710	1470	1,2,5,6, 7,12,20
					20722	CF26DD/E/830/ECO	CFQ26W/G24Q/830	50	12000	3000	82	1710	1470	1,2,5,6, 7,12,20
					20673	CF26DD/E/835/ECO	CFQ26W/G24Q/835	50	12000	3500	82	1710	1470	1,2,5,6, 7,12,20
					20669	CF26DD/E/841/ECO	CFQ26W/G24Q/841	50	12000	4100	82	1710	1470	1,2,5,6, 7,12,20

### DULUX T PREHEAT 2-PIN ECOLOGIC® COMPACT FLUORESCENT LAMPS

With starter in Lamp Base for Magnetic Ballast

Nominal Wattage	Bulb	MOL		Base	Product Number	Ordering Abbreviation	NEMA Generic Designation	Pkg Qty	Avg Rated Life (hrs)	CCT (K)	CRI	Approx Lumens @25°C/77°F		Symbols & Footnotes
		(in)	(mm)									Initial	Mean	
18	T (T4)	4.8	123	GX24D-2	20756	CF18DT/827/ECO	CFTR18W/GX24D/827	50	12000	2700	82	1200	1032	1,4,6,11, 12,20,22
26	T (T4)	5.4	138	GX24D-3	20752	CF26DT/827/ECO	CFTR26W/GX24D/827	50	12000	2700	82	1800	1548	1,4,6,11, 12,20,22

### DULUX T/E 4-PIN ECOLOGIC® COMPACT FLUORESCENT LAMPS

For dimming and electronic ballast. Lamps have End-of-Lamp Life (EOL) Protection

Nominal Wattage	Bulb	MOL		Base	Product Number	Ordering Abbreviation	NEMA Generic Designation	Pkg Qty	Avg Rated Life (hrs)	CCT (K)	CRI	Approx Lumens @25°C/77°F		Symbols & Footnotes
		(in)	(mm)									Initial	Mean	
13	T (T4)	4.2	106	GX24Q-1	20891	CF13DT/E/827/ECO	CFTR13W/GX24Q/827	50	12000	2700	82	900	774	1,2,5,6, 7,12,20
					20892	CF13DT/E/830/ECO	CFTR13W/GX24Q/830	50	12000	3000	82	900	774	1,2,5,6, 7,12,20
					20893	CF13DT/E/835/ECO	CFTR13W/GX24Q/835	50	12000	3500	82	900	774	1,2,5,6, 7,12,20
					20894	CF13DT/E/841/ECO	CFTR13W/GX24Q/841	50	12000	4100	82	900	774	1,2,5,6, 7,12,20
18	T (T4)	4.6	116	GX24Q-2	20760	CF18DT/E/827/ECO	CFTR18W/GX24Q/827	50	12000	2700	82	1200	1032	1,2,5,6, 7,12,20