



# Sealed Lead-Acid Battery

UPG No. 45825

# UB12550

Maintenance-Free

Absorbant Glass Mat (AGM) technology for superior performance. Valve regulated, spill proof construction allows safe operation in any position. Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified. U.L. recognized under file number MH 20567.



## Specification

<b>Nominal Voltage</b>	12 volts			
<b>Nominal Capacity</b>	77° F (25° C)			
20-hr. (12.50A)	55 Ah			
10-hr. (23.25A)	51.15 Ah			
5-hr. (42.50A)	46.75 Ah			
1-hr. (150.00A)	33.00 Ah			
<b>Approximate Weight</b>	35.9 lbs (16.3 kgs)			
<b>Internal Resistance (approx.)</b>	10mΩ			
<b>Shelf Life</b> (% of normal capacity at 77° F (25° C))				
3 Months	6 Months	12 Months		
91%	82%	64%		
<b>Temperature Dependency of Capacity</b>	(20 hour rate)			
104° F	77° F	32° F	5° F	
102%	100%	85%	65%	

## Charge Method (Constant Voltage)


## Cycle Use (Repeating Use)

Initial Current	19.5 A or smaller
Control Voltage	14.5 - 14.9 V

## Float Use


Control Voltage	13.6 - 13.8 V
-----------------	---------------

## Physical Dimensions: in (mm)



**L:** 20.47in (519.9 mm)  
**W:** 10.55in (268 mm)  
**H:** 8.66in (220 mm)  
**TH:** 9.65in (245.1 mm)  
 Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.

## Terminals



### Z Series (Z Post Terminal)

Dimension Type	∅	∅1	H	h
Z1	17.0	8.0	21.5	9.0



### I Series (Internal Thread Terminal)

Dimension Type	∅	H
I4	15	4

## Constant Current Discharge Characteristics Unit:A (25°C, 77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.60V	182.8	133.4	93.9	56.8	29.6	17.3	12.7	9.9	8.2	5.7	5.2	2.8
10.20V	161.0	121.5	84.0	53.8	27.9	16.5	12.4	9.6	8.0	5.6	5.0	2.7
10.50V	155.1	115.6	79.0	52.4	27.2	16.1	12.1	9.5	7.9	5.6	4.9	2.7
10.80V	149.2	109.7	74.1	50.9	26.2	15.7	11.8	9.3	7.7	5.4	4.9	2.7
11.10V	143.3	103.7	69.2	49.4	25.2	15.3	11.4	9.0	7.5	5.3	4.7	2.5

## Constant Power Discharge Characteristics Unit:W (25°C, 77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.60V	1940.9	1465.7	996.9	603.2	343.3	200.1	147.2	114.6	94.4	66.7	60.3	32.5
10.20V	1787.8	1349.1	932.2	597.7	322.6	191.2	143.3	111.6	94.1	65.2	58.8	31.6
10.50V	1759.1	1311.1	896.1	593.8	312.2	186.7	139.8	109.7	91.4	64.7	57.8	31.2
10.80V	1736.4	1276.5	862.5	592.3	303.8	182.8	136.8	107.7	89.9	63.2	57.3	31.1
11.10V	1704.8	1234.5	823.0	587.9	299.9	182.3	135.4	107.2	89.4	62.7	55.8	30.1



ISO 9001 :2008

VR021810


www.upgi.com

1720 Hayden Drive | Carrollton, Texas 75006 | P 469.892.1122 | T 866.892.1122 | F 469.892.1123 | sales@upgi.com


# UB12550

Maintenance-Free


## Discharge Time vs. Discharge Current




## Discharge Characteristics




## Shelf Life & Storage




## Cycle Life vs Depth of Discharge



## Open Circuit Voltage vs Residual Capacity



## Effect of Temperature on Capacity



## Charge Current & Final Discharge Voltage

Application	Charge Voltage(V/Cell)			Max.Charge Current	Final Discharge Voltage V/Cell	Discharge Current(A)	1.75	1.70	1.60	1.30
	Temperature	Set Point	Allowable Range							
Cycle Use	25°C(77°F)	2.45	2.40~2.50	0.35C						
Standby	25°C(77°F)	2.325	2.30~2.35			0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C	



ISO 9001 :2008

Let UPG Power Your Life.

www.upgi.com