



ADVENTURE POWER®

UPG No. 41526

6N11A-1B

Conventional Battery


This battery is specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS, high vibration resistant and long cycle life.

Specification

Nominal Voltage	6 Volts
Nominal Capacity (10H-R)	11 Ah
Approximate Weight (With Acid)	3.97 lbs. (1.8 kgs)
Recommended Maximum Charging Current Limit	3.3A
Equalization and Cycle Service	7.4 VDC/unit Average at 25°C
Cycle Life (JIS D 5302:2004)	225
Terminal Type	F



Physical Dimensions: in (mm)



L: 4.80" (122mm) **H:** 5.16" (131mm) **W:** 2.44" (62mm)
All data subject to change without notice.

Terminal Configuration



Polarity



Exhaust



Front



Side



Terminals

Filling Instructions

- Before filling, ensure your new battery is the correct size for your vehicle.
- Once the battery is filled, it cannot be returned to vendor.
- Only use the acid pack that comes with your battery.
- Fill all cells to the "FULL" mark and wait 30 minutes.
- After 30 minutes, any cell that has settled below the "FULL" mark should be topped off to the "FULL" mark.
- Replace the sealer caps before charging the battery.

Charging Instructions

- Charge the battery fully before installing.
- Never charge this battery with a charger that delivers more than 3 amps of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the 6V 500mah dual stage regulated battery charger.
- This charger/ maintainer can remain connected to the battery indefinitely.

www.upgi.com