



ADVENTURE POWER[®]

UPG No. 41513

This battery is specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS, high vibration resistant and long cycle life.

6N4B-2A

Conventional Battery

Specification

Nominal Voltage	6 Volts
Nominal Capacity (10H-R)	4 Ah
Approximate Weight (With Acid)	1.76lbs. (0.80 kgs)
Recommended Maximum Charging Current Limit	1.2A
Equalization and Cycle Service	7.4 VDC/unit Average at 25°C
Cycle Life (JIS D 5302:2004)	375
Terminal Type	R



Physical Dimensions: in (mm)

<p>L: 3.86" (98mm) H: 3.70" (94mm) W: 1.77" (45mm) All data subject to change without notice.</p>	Terminal Configuration 	Polarity Exhaust
--	-----------------------------------	---



Front



Side



Terminals

Filling Instructions

- Before filling, ensure your new battery is the correct size for your vehicle.
- Once the battery is filled, it cannot be returned to vendor.
- Only use the acid pack that comes with your battery.
- Fill all cells to the "FULL" mark and wait 30 minutes.
- After 30 minutes, any cell that has settled below the "FULL" mark should be topped off to the "FULL" mark.
- Replace the sealer caps before charging the battery.

Charging Instructions

- Charge the battery fully before installing.
- Never charge this battery with a charger that delivers more than 1 amp of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the 6V 500mah dual stage regulated battery charger.
- This charger/ maintainer can remain connected to the battery indefinitely.

www.upgi.com

1720 Hayden Drive | Carrollton, Texas 75006 | P 469.892.1122 | T 866.892.1122 | F 469.892.1123 | sales@upgi.com

VR110509