



ADVENTURE POWER[®]

UPG No. 41527

B54-6

Conventional Battery

This battery is specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS, high vibration resistant and long cycle life.

Specification

Nominal Voltage	6 Volts
Nominal Capacity (10H-R)	12 Ah
Approximate Weight (With Acid)	4.19 lbs. (1.9 kgs)
Recommended Maximum Charging Current Limit	3.6A
Equalization and Cycle Service	7.4 VDC/unit Average at 25°C
Cycle Life (JIS D 5302:2004)	250
Terminal Type	F



Physical Dimensions: in (mm)

L: 6.14" (156mm) **H:** 4.57" (116mm) **W:** 2.24" (57mm)
All data subject to change without notice.

Terminal Configuration

Polarity

Exhaust



Front



Side



Terminals

Filling Instructions

- ⦿ Before filling, ensure your new battery is the correct size for your vehicle.
- ⦿ Once the battery is filled, it cannot be returned to vendor.
- ⦿ Only use the acid pack that comes with your battery.
- ⦿ Fill all cells to the "FULL" mark and wait 30 minutes.
- ⦿ After 30 minutes, any cell that has settled below the "FULL" mark should be topped off to the "FULL" mark.
- ⦿ Replace the sealer caps before charging the battery.

Charging Instructions

- ⦿ Charge the battery fully before installing.
- ⦿ Never charge this battery with a charger that delivers more than 4 amps of current. Larger chargers will harm the battery.
- ⦿ For optimum performance, UPG recommends charging and maintaining with the 6V 500mah dual stage regulated battery charger.
- ⦿ This charger/ maintainer can remain connected to the battery indefinitely.

www.upgi.com