



# ADVENTURE POWER®

UPG No. 42519

## UB12AL-A Conventional Battery


This battery is specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS, high vibration resistant and long cycle life.

### Specification

Nominal Voltage	12 Volts
Nominal Capacity (10H-R)	12 Ah
Approximate Weight (With Acid)	8.38 lbs. (3.8 kgs)
Recommended Maximum Charging Current Limit	3.6A
Equalization and Cycle Service	14.8 VDC/unit Average at 25°C
Cycle Life (JIS D 5302:2004)	250
Terminal Type	F



### Physical Dimensions: in (mm)



**L:** 5.24" (133mm) **H:** 6.30" (160mm) **W:** 3.15" (80mm)  
All data subject to change without notice.

### Terminal Configuration



### Polarity



### Exhaust



Front



Side



Terminals

### Filling Instructions

- Before filling, ensure your new battery is the correct size for your vehicle.
- Once the battery is filled, it cannot be returned to vendor.
- Only use the acid pack that comes with your battery.
- Fill all cells to the "FULL" mark and wait 30 minutes.
- After 30 minutes, any cell that has settled below the "FULL" mark should be topped off to the "FULL" mark.
- Replace the sealer caps before charging the battery.

### Charging Instructions

- Charge the battery fully before installing.
- Never charge this battery with a charger that delivers more than 4 amps of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the Energizer® Maintainer 4000 battery charger.
- This charger/ maintainer can remain connected to the battery indefinitely.

[www.upgi.com](http://www.upgi.com)