



# ADVENTURE POWER<sup>®</sup>

UPG No. 42037

## 51913-22

Sealed AGM Battery

The battery is constructed by plates, separators, safety valves and container. Since the electrolyte is held by a glassmate separator and plates, the battery can be used without leakage. It's specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS and high vibration resistant.

### Specification

<b>Nominal Voltage</b>	12 Volts
<b>Nominal Capacity (10H-R)</b>	22 Ah
<b>Approximate Weight (With Acid)</b>	13.23 lbs. (6 kgs)
<b>Recommended Maximum Charging Current Limit</b>	6.6A
<b>Equalization and Cycle Service</b>	14.8 VDC/unit Average at 25°C
<b>Cycle Life (JIS D 5302:2004)</b>	
<b>Terminal Type</b>	IT



### Physical Dimensions: in (mm)

**L: 7.13" (181mm) H: 6.57" (167mm) W: 3.03" (77mm)**  
All data subject to change without notice.

#### Terminal Configuration

#### Polarity



Front



Side



Terminals

### Charging Instructions

- Ensure your battery is the correct size for your vehicle.
- This battery is sealed at the factory and is maintenance-free. DO NOT attempt to open to fill this battery.
- Charge the battery fully before installing.
- Never charge the battery with a charger that delivers more than 6 amps of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the Energizer<sup>®</sup> Maintainer 4000 battery charger.
- This charger maintainer can remain connected to the battery indefinitely.

*Energizer<sup>®</sup> and the related graphics are trademarks of Eveready Battery Company, Inc. and are used under license by UPG.*

[www.upgi.com](http://www.upgi.com)

1720 Hayden Drive | Carrollton, Texas 75006 | P 469.892.1122 | T 866.892.1122 | F 469.892.1123 | [sales@upgi.com](mailto:sales@upgi.com)