



ADVENTURE POWER[®]

UPG No. 42009

UT5L

Sealed AGM Battery

The battery is constructed by plates, separators, safety valves and container. Since the electrolyte is held by a glassmate separator and plates, the battery can be used without leakage. It's specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS and high vibration resistant.

Specification

| | |
|---|-------------------------------|
| Nominal Voltage | 12 Volts |
| Nominal Capacity (10H-R) | 4 Ah |
| Approximate Weight (With Acid) | 4.19 lbs. (1.9 kgs) |
| Recommended Maximum Charging Current Limit | 1.2A |
| Equalization and Cycle Service | 14.8 VDC/unit Average at 25°C |
| Cycle Life (JIS D 5302:2004) | |
| Terminal Type | D |



Physical Dimensions: in (mm)

L: 4.49" (204mm) **H:** 4.21" (107mm) **W:** 2.76" (70mm)
All data subject to change without notice.

Terminal Configuration

Polarity



Front



Side



Terminals

Charging Instructions

- Ensure your battery is the correct size for your vehicle.
- This battery is sealed at the factory and is maintenance-free. DO NOT attempt to open to fill this battery.
- Charge the battery fully before installing.
- Never charge the battery with a charger that delivers more than 1 amp of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the Energizer[®] Maintainer 1000 battery charger.
- This charger maintainer can remain connected to the battery indefinitely.

Energizer[®] and the related graphics are trademarks of Eveready Battery Company, Inc. and are used under license by UPG.

www.upgi.com

1720 Hayden Drive | Carrollton, Texas 75006 | P 469.892.1122 | T 866.892.1122 | F 469.892.1123 | sales@upgi.com