



ADVENTURE POWER[®]

UPG No. 43006

UTX7L-BS

Dry Charge AGM Battery

This battery is specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS, high vibration resistant and long cycle life.



Specification

Nominal Voltage	12 Volts
Nominal Capacity (10H-R)	6 Ah
Approximate Weight (With Acid)	4.85 lbs. (2.2 kgs)
Recommended Maximum Charging Current Limit	1.8A
Equalization and Cycle Service	14.8 VDC/unit Average at 25°C
Cycle Life (JIS D 5302:2004)	
Terminal Type	D

Physical Dimensions: in (mm)

L: 4.41" (112mm) **H:** 5.04" (128mm) **W:** 2.76" (70mm)
All data subject to change without notice.

Terminal Configuration

Polarity



Front



Side



Terminals

Filling Instructions

- ⦿ Before filling, ensure your new battery is the correct size for your vehicle. Once the battery is filled, it cannot be returned to vendor.
- ⦿ Only use the acid pack that comes with your battery.
- ⦿ Remove the sealing plugs from electrolyte cells on the battery.
- ⦿ Remove filler cap strip from electrolyte bottle to expose silver foils. DO NOT remove silver foils.
- ⦿ Push the bottle down into the cells piercing the seals. Fill your battery with all the contents of the acid pack.
- ⦿ The bottle contains the exact amount of electrolyte needed for the battery. DO NOT add water.
- ⦿ After the filling, replace the sealing plugs on each battery cell. Do not remove the sealing plugs for charging.

Charging Instructions

- ⦿ Charge the battery fully before installing.
- ⦿ Never charge this battery with a charger that delivers more than 2 amps of current. Larger chargers will harm the battery.
- ⦿ For optimum performance, UPG recommends charging and maintaining with the Energizer[®] Maintainer 2000 battery charger.
- ⦿ This charger maintainer can remain connected to the battery indefinitely.

Energizer[®] and the related graphics are trademarks of Eveready Battery Company, Inc. and are used under license by UPG.

www.upgi.com