



ADVENTURE POWER[®]

UPG No. 42016

UTZ14S

Sealed AGM Battery

The battery is constructed by plates, separators, safety valves and container. Since the electrolyte is held by a glassmate separator and plates, the battery can be used without leakage. It's specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS and high vibration resistant.

Specification

Nominal Voltage	12 Volts
Nominal Capacity (10H-R)	11.2 Ah
Approximate Weight (With Acid)	7.94 lbs. (3.6 kgs)
Recommended Maximum Charging Current Limit	3.4A
Equalization and Cycle Service	14.8 VDC/unit Average at 25°C
Cycle Life (JIS D 5302:2004)	
Terminal Type	K



Physical Dimensions: in (mm)

L: 5.91" (150mm) **H:** 4.33" (110mm) **W:** 3.43" (87mm)
All data subject to change without notice.

Terminal Configuration

Polarity



Front



Side



Terminals

Charging Instructions

- Ensure your battery is the correct size for your vehicle.
- This battery is sealed at the factory and is maintenance-free. DO NOT attempt to open to fill this battery.
- Charge the battery fully before installing.
- Never charge the battery with a charger that delivers more than 3 amps of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the Energizer[®] Maintainer 2000 battery charger.
- This charger maintainer can remain connected to the battery indefinitely.

Energizer[®] and the related graphics are trademarks of Eveready Battery Company, Inc. and are used under license by UPG.

www.upgi.com

1720 Hayden Drive | Carrollton, Texas 75006 | P 469.892.1122 | T 866.892.1122 | F 469.892.1123 | sales@upgi.com