



ADVENTURE POWER[®]

UPG No. 42010

UTZ7S

Sealed AGM Battery

The battery is constructed by plates, separators, safety valves and container. Since the electrolyte is held by a glassmate separator and plates, the battery can be used without leakage. It's specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS and high vibration resistant.

Specification

Nominal Voltage	12 Volts
Nominal Capacity (10H-R)	6 Ah
Approximate Weight (With Acid)	4.41 lbs. (2 kgs)
Recommended Maximum Charging Current Limit	1.8A
Equalization and Cycle Service	14.8 VDC/unit Average at 25°C
Cycle Life (JIS D 5302:2004)	
Terminal Type	D



Physical Dimensions: in (mm)

	<h4>Terminal Configuration</h4>	<h4>Polarity</h4>
<p>L: 4.49" (204mm) H: 4.21" (107mm) W: 2.76" (70mm) All data subject to change without notice.</p>		



Front



Side



Terminals

Charging Instructions

- Ensure your battery is the correct size for your vehicle.
- This battery is sealed at the factory and is maintenance-free. DO NOT attempt to open to fill this battery.
- Charge the battery fully before installing.
- Never charge the battery with a charger that delivers more than 2 amps of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the Energizer[®] Maintainer 2000 battery charger.
- This charger maintainer can remain connected to the battery indefinitely.

Energizer[®] and the related graphics are trademarks of Eveready Battery Company, Inc. and are used under license by UPG.

www.upgi.com

1720 Hayden Drive | Carrollton, Texas 75006 | P 469.892.1122 | T 866.892.1122 | F 469.892.1123 | sales@upgi.com