



Product Number: 64843

Order Abbreviation: MCP150/PAR38/U/830/VWFL/ECO PB

General Description: 150W, high CRI, ceramic arc tube, reduced color shift, high performance, open fixture rated Par38 Metal Halide Lamp, clear, very wide flood

Product Information

Abbrev. With Packaging Info.	MCP150PAR38U830VWFLECO PB 6/CS 1/SKU
Approx. Lumens (initial - horizontal)	9100
Approx. Lumens (initial - vertical)	9100
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Avg Rated Life (hrs)	15000
Base	E26 Medium
Beam Angle (deg)	65
Beam Type	VWFL
Bulb	PAR38
Centerbeam Candlepower (cp)	6500
Color Rendering Index (CRI)	88
Color Temperature/CCT (K)	3000
Diameter (in)	4.760
Diameter (mm)	121.00
Family Brand Name	Metalarc® Powerball
Fixture Requirement	O
Hot Restrike Time (min)	4-6
Lamp Finish	Coated
Maximum Base Temperature - Fahrenheit	374
Maximum Base Temperature - Celsius	190
Maximum Bulb Temperature - Fahrenheit	662
Maximum Bulb Temperature - Celsius	350
Maximum Overall Length - MOL (in)	5.32
Maximum Overall Length - MOL (mm)	135
Nominal Voltage (V)	95.00
Nominal Wattage (W)	150.00
Operating Position	Universal

Warm-up Time (min)	2-4
--------------------	-----



ECOLOGIC

TM

**Footnotes**

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- Passes Federal TCLP test based on NEMA LL Series Standards. TCLP data available upon request. Disposal regulations may vary depending on location. Please check your local and state/provincial regulations.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaires. See lamp warning.
- Lamps may be operated on a M142 Compliant ballast.
- Lamps with a E26 medium skirt base are not compatible with exclusionary medium sockets.