



**Product Number:** 64773

**Order Abbreviation:** MP175/BU-ONLY

**General Description:** 175W open fixture rated metal halide lamp, clear, base up within 15deg

#### Product Information

Abbrev. With Packaging Info.	MP175BUONLY 6/CS 1/SKU
ANSI Code	M57/O
Approx. Lumens (initial - vertical)	14400
Approx. Lumens (mean - vertical)	10200
Arc Length (in)	1.12
Arc Length (mm)	28.5
Average Rated Life - Vertical (hr)	10000
Base	EX39 Exclusionary Mogul
Bulb	BT28
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	3.500
Diameter (mm)	89.00
Family Brand Name	Metalarc Pro-Tech®
Fixture Requirement	O
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.31
Maximum Overall Length - MOL (mm)	211
Nominal Voltage (V)	132.00
Nominal Wattage (W)	175.00
Operating Position	Base up within 15deg only
Warm-up Time (min)	2-4

#### Footnotes

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.