



Product Number: 64201

Order Abbreviation: MCP70PAR30LN/U/930/SP/ECO PB

General Description: 70W high CRI, powerball arc tube, reduced color shift, high performance, ECO open fixture rated Par30 Metal Halide Lamp, spot

Product Information

| | |
|---------------------------------------|----------------------------------------|
| Abbrev. With Packaging Info. | MCP70PAR30LNU930SPECOPB 90V 6/CS 1/SKU |
| ANSI Code | C139/O:C98/O |
| Approx. Lumens (initial - horizontal) | 3400 |
| Approx. Lumens (initial - vertical) | 3400 |
| Average Rated Life - Horizontal (hr) | 12000 |
| Average Rated Life - (hr) | 12000 |
| Avg Rated Life (hrs) | 12000 |
| Base | E26 Medium |
| Beam Angle (deg) | 12 |
| Beam Type | SP |
| Bulb | PAR30LN |
| Centerbeam Candlepower (cp) | 42000 |
| Color Rendering Index (CRI) | 95 |
| Color Temperature/CCT (K) | 3000 |
| Diameter (in) | 3.752 |
| Diameter (mm) | 95.30 |
| Family Brand Name | Metalarc® Powerball |
| Fixture Requirement | O |
| Hot Restrike Time (min) | 4-6 |
| Lamp Finish | Clear |
| Maximum Base Temperature - Fahrenheit | 410 |
| Maximum Base Temperature - Celsius | 210 |
| Maximum Bulb Temperature - Fahrenheit | 572 |
| Maximum Bulb Temperature - Celsius | 300 |
| Maximum Overall Length - MOL (in) | 4.76 |
| Maximum Overall Length - MOL (mm) | 121 |
| Nominal Voltage (V) | 90.00 |
| Nominal Wattage (W) | 70.00 |

| | |
|--------------------|-----------|
| Operating Position | Universal |
| Warm-up Time (min) | 2-4 |



ECOLOGIC

™



Footnotes

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- Passes Federal TCLP test based on NEMA LL Series Standards. TCLP data available upon request. Disposal regulations may vary depending on location. Please check your local and state/provincial regulations.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaires. See lamp warning.
- Lamp requires a nominal Open Circuit Voltage of 230V or higher. Without an ignitor in the circuit minimum OCV is 209Vrms.
- Lamps may be operated on ANSI M98 Compliant Ballast.
- UV-Stop quartz