

EnduraLED 16W 4200K 120V PAR38

Product family description

The Philips EnduraLED™ PAR indoor reflectors with high brightness LEDs are suited for track and recessed lighting. Energy saving, long life LED PAR lamps install into existing fixtures, can lower cost with reduced wattage and relamping frequency.

Features

- · Soft white light.
- · Ideal for overhead track fixtures.
- · High brightness indoor flood lamps.
- Application performance close to 45W Halogen PAR.
- Offers 15 year rated average life, if operated 8 hours per day, 7 days per week.
- Smooth dimming to 10% of full light levels (Designed for "Leading Edge" TRIAC dimming systems)
- 16Watt Par38 in Soft White, Warm White, and Cool White versions.

Benefits

- Philips is the global leader in light and a leader in LED technology.
- Philips knows LED light and stands behind the EnduraLED products with a warranty.
- Philips' commitment to innovation and quality provides the confidence of partnering with an industry leader.

Application

· Perfect for track and recessed lighting.


Product data		
Product Number	406793	
Full product name	EnduraLED 16W 4200K 120V PAR38	
Ordering Code	406793	
Pack type		
Pieces per Sku		
Skus/Case	6	
Pack UPC	046677406790	



Product data		
EAN2US		
Case Bar Code	50046677406795	
Successor Product number		
Bulb	PAR38 [PAR38 mm]	
Average Lifetime	45000 hr	
Pack UPC	046677406790	
Case Bar Code	50046677406795	
Ordering Code	16PAR38/END/FL25 4200 120V	
Wattage	I6W	
Color Code	CW	
Color Designation (text)	Cool White	
Correlated Color Temperature	4200 K	
Luminous Flux	850 Lm	
Luminous Intensity	4000 cd	
Color rendering index	65	
Color Temperature	4200K [CCT 4200K]	
Product Number	406793	



EnduraLED E26 PAR38



EnduraLED E26/E27 PAR38 Dimmable/Outdoor



©2009 Koninklijke Philips Electronics N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liablity will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Document order number : 0000 000 00000