



PRODUCTS

PRODUCT DEVEL

- Aquarium
- AV/Photographic
- Cinema
- Entertainment
- General Lighting
- Graphic Arts
- Heater/IR
- Horticulture
- Miniature
- Scientific-Medical
- Semiconductor
- UV
- Lamp & Ballast Recycling



[Products](#) > Product Data Specs - More Info.

## Product Data Specs - More Info.

USHIO Product Data Specs - More Info.



Lamp Photo



[Report broken links or errors](#)

[Share](#) |

Email this page to a friend

Enter email address

ushio.com/products/datasearch.htm

USHIO Code#	3000238
USHIO Lamp Series	ULTRA CFL
Product ID/ANSI Code	CF26DE/865
Description	CF26DE/865, Double Tube
Rating	26W 6500K 85CPL C210 2

[REQUEST FOR A QUOTE](#)  
[NEW SEARCH](#)

Description 2	Z6VV 0500K 85CRI G24Q-3
Item Market	General Illumination
Item Type	Fluorescent
Item Prefix	CFL
Base	G24Q3
Voltage	105.0
Wattage	26.0
Amperage	0.325
Burn Position	ANY
Bulb Shape	T4D
Bulb Finish	INPHOS
CRI	85
Color Temp (K)	6,500
Arc Gap (mm)	N/A
Ballast	N/A
Beam Angle	
Beam Spread	N/A
Candle Power (cd)	
Contact to Contact (mm)	N/A
Efficacy (lm/W)	65.8
Filament	N/A
Front Glass Cover	NO
Initial Lumens (lm)	N/A
Mean Lumens (lm)	1710
Luminous Flux (lm)	1710
Life (hr )	10,000
Life Commercial (hr)	12500
Diameter (mm )	12.70
MOL (mm)	165.00
Light Center Length (mm)	N/A
Lighted Length (lm)	N/A
Reflector Size (mm)	
Reflector Type	N/A
Working Distance (mm)	N/A
Spectral Range	N/A
Ozone Free	YES
UV Protected	N/A
Case Qty	50
Download brochure	<a href="#">CompactFluorescent.pdf</a>

Back

Data specs. are subject to change without prior notice.

[back to top](#)

Get Connected and follow us  
on Facebook and Twitter



[Product Lamps](#)  
[Power Supplies](#)  
[Product Catalog](#)  
[Product Data Specs. Search](#)  
[Annual Energy Savings / ROI  
Calculator](#)

[Press Releases](#)  
[News and Events](#)  
[Excimer Sources](#)  
[U-eLektron EBeam Sources](#)  
[Industry Systems & Apps](#)

[Lamp](#)  
[Lamp](#)  
[Our P](#)  
[Envirc](#)  
[FAQs](#)

©2011 USHIO America, Inc. All rights reserved.

(800) 838-7446 | [Privacy Policy](#)