



Modular Electronic Time Controls



FM1D20A



FM1D20E



FM2D50



0.1 lbs
0.05 kg
-14°F
(-40°C)
to
131°F
(68°C)

FM1D – A and E Series 24-hour and/or 7-Day

Wiring connections:

- "A" Models: screw terminals for #10 to #24 AWG wire
- "E" Models: 1/4 in. quick connects

| Model # | Voltage | # of Circuits | Switch Rating | Programs | Mounting |
|-------------|------------|---------------|---------------|----------|------------------|
| FM1D20A-120 | 120 VAC | 1 | SPDT, 16 Amp | 20 | Surface/DIN Rail |
| FM1D20A-24 | 24 VAC/VDC | 1 | SPDT, 16 Amp | 20 | Surface/DIN Rail |
| FM1D20A-240 | 240 VAC | 1 | SPDT, 16 Amp | 20 | Surface/DIN Rail |
| FM1D20E-120 | 120 VAC | 1 | SPDT, 16 Amp | 20 | Flush |
| FM1D20E-24 | 24 VAC/VDC | 1 | SPDT, 16 Amp | 20 | Flush |
| FM1D20E-240 | 240 VAC | 1 | SPDT, 16 Amp | 20 | Flush |
| FM1D50A-12 | 12 VAC/VDC | 1 | SPDT, 16 Amp | 50 | Surface/DIN Rail |
| FM1D50A-120 | 120 VAC | 1 | SPDT, 16 Amp | 50 | Surface/DIN Rail |
| FM1D50A-24 | 24 VAC/VDC | 1 | SPDT, 16 Amp | 50 | Surface/DIN Rail |
| FM1D50A-240 | 240 VAC | 1 | SPDT, 16 Amp | 50 | Surface/DIN Rail |
| FM1D50E-12 | 12 VAC/VDC | 1 | SPDT, 16 Amp | 50 | Flush |
| FM1D50E-120 | 120 VAC | 1 | SPDT, 16 Amp | 50 | Flush |
| FM1D50E-24 | 24 VAC/VDC | 1 | SPDT, 16 Amp | 50 | Flush |
| FM1D50E-240 | 240 VAC | 1 | SPDT, 16 Amp | 50 | Flush |

FM2D50 Series 24-hour and/or 7-day

Dual circuit timer allows for each circuit to be programmed separately or together

| Model # | Volts AC | # of Circuits | Switch Rating | Programs | Mounting |
|-------------|----------|---------------|---------------|----------|------------------|
| FM2D50-120* | 120 | 2 | SPDT, 16 Amp | 50 | Flush or surface |
| FM2D50-24* | 24 | 2 | SPDT, 16 Amp | 50 | Flush or surface |
| FM2D50-240* | 240 | 2 | SPDT, 16 Amp | 50 | Flush or surface |

* For DIN rail Mounting, order accessory, MB-DIN (DIN Rail Mounting Base).