


PAR20 SERIES

- Crisp white light
- Directional light source
- Long life
- Available in 120/130V

Watts	Bulb	Base	Item#	Description	Voltage (V)	Case Qty.	Dimension MOL (in)	Dimension Dia (in)	Approx Lumens (lm)	Beam Angle	Spread	Avg.Life (Hours)	Manufacture Production Code
PAR20 Series - Medium Screw Base													
35	PAR20	E26	3090	35PAR20/SP/120	120	15	3.30	2.50	380	10°	Spot	2500	H35772101022
			3093	35PAR20/SP/130	130	15	3.30	2.50	380	10°	Spot	2500	H35772101032
			@ 120 volts approximate 31 watts, 275 lumens, 5000 hours										
			*3091	35PAR20/NFL/120	120	15	3.30	2.50	380	30°	N. Flood	2500	H35772302022
			*3094	35PAR20/NFL/130	130	15	3.30	2.50	380	30°	N. Flood	2500	H35772302032
			@ 120 volts approximate 31 watts, 275 lumens, 5000 hours										
			3092	35PAR20/FL/120	120	15	3.30	2.50	380	40°	Flood	2500	H35772403022
50	PAR20	E26	3095	35PAR20/FL/130	130	15	3.30	2.50	380	40°	Flood	2500	H35772403032
			@ 120 volts approximate 31 watts, 275 lumens, 5000 hours										
			3096	50PAR20/SP/120	120	15	3.30	2.50	550	10°	Spot	2500	H50772101022
			3099	50PAR20/SP/130	130	15	3.30	2.50	550	10°	Spot	2500	H50772101032
			@ 120 volts approximate 44 watts, 470 lumens, 5000 hours										
			3097	50PAR20/NFL/120	120	15	3.30	2.50	550	30°	N. Flood	2500	H50772302022
			3100	50PAR20/NFL/130	130	15	3.30	2.50	550	30°	N. Flood	2500	H50772302032
@ 120 volts approximate 44 watts, 470 lumens, 5000 hours													
3098	50PAR20/FL/120	120	15	3.30	2.50	550	40°	Flood	2500	H50772403022			
3101	50PAR20/FL/130	130	15	3.30	2.50	550	40°	Flood	2500	H50772403032			
@ 120 volts approximate 44 watts, 470 lumens, 5000 hours													

* Items only available for special orders

All measurements are shown in inches unless noted



PAR20
E26 Base