

[Return to search](#)

[Print Page](#)



**Product Number:** 14513  
**Order Abbreviation:** 75PAR38/HAL/FL30 120V  
**General Description:** Tungsten Halogen CAPSYLITE PAR38 Reflector Lamp Medium Skirt Base 75Watt 120Volt Flood Beam

**Product Information**

|                                   |                                 |
|-----------------------------------|---------------------------------|
| Abbrev. With Packaging Info.      | 75PAR38HALFL30 120V 15/CS 1/SKU |
| Approx. Lumens                    | 1060                            |
| Average Rated Life (hr)           | 2500                            |
| Base                              | E26 Medium Skirted              |
| Beam Angle (deg)                  | 30                              |
| Beam Type                         | FL                              |
| Bulb                              | PAR38                           |
| Centerbeam Candlepower (cp)       | 3150                            |
| Class                             | C (gas)                         |
| Color Rendering Index (CRI)       | 100                             |
| Color Temperature/CCT (K)         | 2900                            |
| Diameter (in)                     | 4.75                            |
| Diameter (mm)                     | 120.65                          |
| Ecologic                          | YES                             |
| Family Brand Name                 | CAPSYLITE® PAR38 SPL            |
| Filament                          | CC-8                            |
| Horizontal Beam Angle (deg)       | 30                              |
| Maximum Overall Length - MOL (in) | 5.313                           |
| Maximum Overall Length - MOL (mm) | 134.9375                        |
| Nominal Voltage (V)               | 120.00                          |
| Nominal Wattage (W)               | 75.00                           |
| Vertical Beam Angle (deg)         | 30                              |

**Additional Product Information**

**Product Documents, Graphs, and Images**

**Packaging Information**



**Footnotes**

- State of the Art SPL Optics
- To avoid electric shock and/or skin burns, turn off power and allow bulb to cool before handling or attempting replacement.
- In base up operation, heat may eventually deteriorate paper-lined or plastic sockets.

[Print Page](#)