

[Return to search](#)

[Print Page](#)



**Product Number:** 14515  
**Order Abbreviation:** 75PAR38/HAL/FL30 130V  
**General Description:** Tungsten Halogen CAPSYLITE PAR38 Reflector Lamp Medium Skirt Base 75Watt 130Volt Flood Beam

**Product Information**

Abbrev. With Packaging Info.	75PAR38HALFL30 130V
Approx. Lumens	1060
Average Rated Life (hr)	2500
Base	E26 Medium Skirted
Beam Angle (deg)	30
Beam Type	FL
Bulb	PAR38
Centerbeam Candlepower (cp)	3150
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	2900
Diameter (in)	4.75
Diameter (mm)	120.65
Ecologic	YES
Family Brand Name	CAPSYLITE® PAR38 SPL
Filament	CC-8
Horizontal Beam Angle (deg)	30
Maximum Overall Length - MOL (in)	5.313
Maximum Overall Length - MOL (mm)	134.9375
Nominal Voltage (V)	130.00
Nominal Wattage (W)	75.00
Vertical Beam Angle (deg)	30

**Additional Product Information**

**Product Documents, Graphs, and Images**

**Packaging Information**



**Footnotes**

- State of the Art SPL Optics
- To avoid electric shock and/or skin burns, turn off power and allow bulb to cool before handling or attempting replacement.
- In base up operation, heat may eventually deteriorate paper-lined or plastic sockets.
- Approximate life for 130 volt tungsten halogen lamps operated at 120 volts is within the value calculated using the recommended equations for standard incandescent lamps, as set forth in the IES Handbook, 8th edition. Because of the uncertain nature of the halogen cycle on the coil when operated at less than rated voltage, life of tungsten halogen lamps varies considerably and unpredictably. OSRAM SYLVANIA does not recommend operation at other than rated voltage.
- @ 120 volts, approximate 66 watts, 805 lumens, 5000 hours

[Print Page](#)