

S4




Specifications:

| | |
|-------------------------------|---|
| Maximum Wattage | 1000 W |
| Maximum Voltage | 250 V |
| Maximum Operating Temperature | 300° C |
| Qualifications | UL Recognized – E31557 CSA Certified – LR20904 |
| Body Material | Steatite / Nickel Plated Steel |
| Contact Material | Screw Shell, Center Contact = Nickel Plated Brass |
| Wire Leads | AWG 18 minimum, 600 V/200° C minimum |

LAMP BASE:

Mini-Candelabra Screw
E11



ORDERING INFORMATION

| Product Number | Product Description | Wire Gauge/Type/Color | Wire Length (inches) | Case / SKU Qty Qty |
|----------------|---------------------|-------------------------------|----------------------|--------------------|
| 69785 | S4 | N/A | N/A | 240 / 24 |
| 69657 | S4 | N/A | N/A | 100 / 100 |
| 69656 | S4 6IN/18GA/ULSF2 | AWG18/ULSF2/1 Black, 1 White | 6 | 100 / 100 |
| 69653 | S4 12IN/16GA/UL1199 | AWG16/UL1199/1 Black, 1 White | 12 | 100 / 100 |
| 69654 | S4 18IN/18GA/ULSF2 | AWG18/ULSF2/1 Black, 1 White | 18 | 100 / 100 |
| 69655 | S4 36IN/18GA/ULSF2 | AWG18/ULSF2/1 Black, 1 White | 36 | 100 / 100 |

Made-to-order types.

